

Part Number: 8750

Audio/Control/Instrumentation, (27 pr) 22 AWG (7x30)

TC, PVC/PVC, CMG

# **Product Description**

Twenty-seven 22 AWG stranded (7x30) tinned copper conductors, twisted pairs, PVC insulation, PVC jacket.

# **Product Specifications**

# **Technical Specifications**

# **Construction and Dimensions**

#### Conductor:

AWG	Stranding	Material	No. of Pairs
22	7×30	TC - Tinned Copper	27

Total Number of Conductors:	<b>1</b> 54

#### Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.011 in

#### Color Chart 1:

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green
10	Red & Blue
11	Red & Yellow
12	Red & Brown
13	Red & Orange
14	Green & White
15	Green & Blue
16	Green & Yellow
17	Green & Brown
18	Green & Orange
19	White & Blue
20	White & Yellow
21	White & Brown
22	White & Orange
23	Blue & Yellow
24	Blue & Brown
25	Blue & Orange
26	Brown & Yellow
27	Brown & Orange

## Outershield 1:

Material
Unshielded

# Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.575 in	0.045 in

# **Electrical Characteristics**

### **Conductor DCR:**

#### **Nominal Conductor DCR**

14.7 Ohm/1000ft

## Capacitance:

#### Nom. Capacitance Conductor to Conductor

25.5 pF/ft

#### **Current:**

#### Max. Recommended Current [A]

1.4 Amps per conductor @ 20°C

## Voltage:

UL Description	UL Voltage Rating
UL AWM Style 2576	150 V RMS
сма	300 V RMS

### Use

Max Recommended Pulling Tension:	490 lbs
----------------------------------	---------

# Safety

CSA Flammability:	FT4
UL Flammability:	UL1685 FT4 Loading

# **Temperature Range**

Non-UL Temp Rating:	80°C (UL AWM Style 2576)
Operating Temp Range:	-20°C To +80°C

# **Mechanical Characteristics**

Min Bend Radius/Minor Axis:	5.75 in
-----------------------------	---------

# **Part Number**

Plenum (Y/N):	No

# **Standards**

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification

UL AWM Style:	AWM Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

## **History**

## **Product Variants**

Part Number	Color	Put-Up Type	Length
8750 0601000	CHROME	Reel	1000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in comptiance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.