

Part Number: 9314

300V PLTC, (1 pr) 14 AWG (42x30) TC, PVC/PVC, Foil

Shlo

# **Product Description**

One 14 AWG pair stranded (42x30) tinned copper conductors, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

# **Product Specifications**

# **Technical Specifications**

## **Construction and Dimensions**

#### Conductor:

AWG	Stranding	Material	No. of Pairs
14	42×30	TC - Tinned Copper	1

Total Number of Conductors:

2

#### Insulation:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.119 in	0.022 in

### Color Chart 1:

Number	Color
1	Black & Red

#### Outershield 1:

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	16	19x29 mm

### Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.325 in	0.042 in	Yes

Print Legend:

BELDEN 9314 E34972 1PR14 SHIELDED (UL) CL3R 105C OR PLTC OR ITC SUN RES OR AWM 2464 80C 300V- - -FT4 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET

# **Electrical Characteristics**

#### **Conductor DCR:**

Nominal Conductor DCR	Nominal Outer Shield DCR
2.6 Ohm/1000ft	4.4 Ohm/1000ft

### Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
27 pF/ft	54 pF/ft

#### Inductance:

Nominal Inductance		
0.18 μH/ft		

## Voltage:

UL Voltage Rating	
300 V RMS	

## Use

Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	64 lbs

## **Safety**

CSA Flammability:	FT4
IEEE Flammability:	1202
UL Flammability:	UL1685 UL Loading

## **Temperature Range**

Operating Temp Range:	-30°C To +105°C
operating remp kange.	-30 C 10 105 C

## **Mechanical Characteristics**

Min Bend Radius/Minor Axis:	3.25 in

# **Part Number**

Plenum (Y/N):	No
---------------	----

### **Standards**

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)	
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)	
NEC/(UL) Specification:	NEC/(UL) Specification	
UL AWM Style:	AWM Specification	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	EU CE Mark	

## **History**

### **Product Variants**

Part Number	Color	Put-Up Type	Length
9314 0601000	CHROME	Reel	1000 ft
9314 0605000	CHROME	Reel	5000 ft
9314 060U500	CHROME	UnReel	500 ft

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC