

**Part Number:** 8732Audio/Control/Instrumentation, (2 pr) 22 AWG (7x30)
TC, PE/PVC, (1 pr) TC Braid, CM

Product Description

Two 22 AWG pairs stranded (7x30) TC conductors, polyethylene insulation, conductors cabled, TC braid shield over one pair (62% coverage), PVC jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	2
Total Number of Conductors:			4

Insulation:

Material	Nominal Wall Thickness
PE - Polyethylene	0.021 in

Color Chart 1:

Number	Color
1	Black, Clear
2	Black, Clear

Innershield:

Type	Layer	Material	Coverage [%]
Braid	1st Pair	TC - Tinned Copper	62 %
Unshielded	2nd Pair		

Outershield 1:

Material
Unshielded

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.206 x 0.332 in	0.03 in

Electrical Characteristics

Conductor DCR:

Max. Conductor DCR	Nominal Conductor DCR
10.8 Ohm/1000ft	15.4 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Other Conductor to Shield	Nom. Capacitance Conductor to Shield
21 pF/ft	37 (shielded pair only) pF/ft

Impedance:

Nominal Characteristic Impedance	Nominal Characteristic Impedance Description
74 Ohm	Shielded pair

Current:

Max. Recommended Current [A]
2.3 Amps per conductor @ 25°C

Voltage:

UL Voltage Rating
300 V RMS (UL AWM Style 2094)

Use

Max Recommended Pulling Tension:	59 lbs
----------------------------------	--------

Safety

UL Flammability:	UL1685 UL Loading
------------------	-------------------

Temperature Range

Operating Temp Range:	-20°C To +60°C
UL Temp Rating:	60°C (UL AWM Style 2094)

Mechanical Characteristics

Min Bend Radius/Minor Axis:	2.25 in
-----------------------------	---------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
8732 0601000	CHROME	Reel	1000 ft

© 2016 Belden, Inc.

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.