

PT-102AN

1:2 Stereo Audio Distribution Amplifier





The PT-102AN is a high-performance audio distribution amplifier for unbalanced stereo signals. The unit takes one stereo input and distributes the signal to two identical stereo outputs.

FEATURES

- Level (Gain) Controls.
- S/N Ratio 85dB.
- Ultra-Compact Pico TOOLS™ 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.

TECHNICAL SPECIFICATIONS

INPUT: 1 unbalanced stereo audio on a 3.5mm mini jack.

OUTPUTS: 2 unbalanced stereo audio on 3.5mm mini jacks.

MAX. OUTPUT LEVEL: 5Vpp.

BANDWIDTH (-3dB): >100kHz.

S/N RATIO: 85dB @1kHz.

CONTROLS: Level: -55dB to +20dB.

COUPLING: AC.

AUDIO THD + NOISE: 0.01% @1kHz.

AUDIO 2nd HARMONIC: 0.004% @1kHz.

POWER CONSUMPTION: 12V DC, 20mA.

DIMENSIONS: 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H.

WEIGHT: 0.14kg (0.31lbs) approx.

 ${\tt INCLUDED}\ {\tt ACCESSORIES:}\ Power\ supply,\ mounting\ bracket.$

OPTIONS: RK-4PT 19" rack adapter.

