



Part Number: 83954

Thermocouple Extension, (1 pr) 20 AWG (7x28) Type TX, FEP/FEP, Foil Shld, PLTC, High-Temp

Product Description

One 20 AWG pair stranded (7x28) Type TX conductors, fluorinated ethylene propylene (FEP) insulation, overall Beldfoil® shield (100% coverage), fluorinated ethylene propylene (FEP) jacket.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	No. of Pairs
20	7x28	Copper & Constantan	1
Total Number of Conductors:			2

Insulation:

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.01 in

Color Chart 1:

Number	Color
1	Blue & Red

Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	Beldfoil®	100 %	TC - Tinned Copper	22	7x30 mm

Outerjacket 1:

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	0.145 in

Print Legend:	BELDEN 83954 E34972 1PR20 SHIELDED (UL) CL3P 200C PLTC SUN RES THCPL EXTN TX (2 FT., 7 DIGIT SEQUENTIAL NUMBER) FEET
---------------	--

Electrical Characteristics

Conductor DCR:

Element	Nominal Conductor DCR	Nominal Outer Shield DCR
COPPER	10 Ohm/1000ft	12 Ohm/1000ft
CONSTANTAN	283 Ohm/1000ft	

Use

Safety

UL Flammability:	UL910 Steiner Tunnel
------------------	----------------------

Temperature Range

Non-UL Temp Rating:	200°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	1.5 in
-----------------------------	--------

Part Number

Plenum (Y/N):	Yes
---------------	-----

Standards

ANSI Compliance:	ANSI Specification
CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

History

Product Variants

Part Number	Color	Put-Up Type	Length
83954 0061000	BLUE, LIGHT	Reel	1000 ft

© 2016 Belden, Inc.
All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.