



Part Number: 9916

UL AWM Style 1007 and 1569

# **Product Description**

Tinned copper conductor, PVC insulation. Rated 105°C, 300V. Rated 600V peak for electronic circuits, and internal wiring for electronic and electrical equipment.

## **Product Specifications**

# **Technical Specifications**

## **Construction and Dimensions**

#### Conductor:

AWG	Stranding	Material	No. of Conductors	No. of Pairs
16	26x30	TC - Tinned Copper	1	6
			6	

Total Number of Conductors:	1

### Insulation:

Material	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.016 in	0.015 in

### Color Chart 1:

Number		
6		

#### Cabling 1:

wists	1
twist/ft	

### Outerjacket 1:

#### **Nominal Diameter**

0.092 in

## **Electrical Characteristics**

## High Freq:

### Max. Insertion Loss (Attenuation)

6 db/100m

### Use

## Safety

CSA Flammability:	FT1
UL Flammability:	VW-1

## **Temperature Range**

## **Mechanical Characteristics**

### **Part Number**

### **Standards**

CA Prop 65 (CJ for Wire & Cable):	Yes	
CSA Rating:	300V RMS, 105°C	
CSA Type:	TRSR-64	
MII Order #39 (China RoHS):	Yes	
UL AWM Style:	UL Style 1007 (300V 80°C)^UL Style 1569 (300V 105°C)	
UL Rating:	300V RMS, 80°C and 300V, 105°C	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	Yes	

## History

## **Product Variants**

Part Number	Color	Put-Up Type	Length
9916	1-5, 7-10, 13		

9916	1-5, 7-10, 13		
9916 0011000	BROWN	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 001100	BROWN	Reel	100 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0021000	RED	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 002100	RED	Reel	100 ft
9916	1-5, 7-10, 13		
9916 0025000	RED	Reel	5000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0031000	ORANGE	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0041000	YELLOW	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 004100	YELLOW	Reel	100 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0051000	GREEN, DARK	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 005100	GREEN, DARK	Reel	100 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0071000	VIOLET	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 007100	VIOLET	Reel	100 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0081000	GRAY	Reel	1000 ft

9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0091000	WHITE	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 009100	WHITE	Reel	100 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0095000	WHITE	Reel	5000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0101000	BLACK	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 010100	BLACK	Reel	100 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0105000	BLACK	Reel	5000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 0131000	BLUE, DARK	Reel	1000 ft
9916	1-5, 7-10, 13		
9916	1-5, 7-10, 13		
9916 013100	BLUE, DARK	Reel	100 ft

#### © 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in comptiance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.