



Aluminum Splice T&B Catalog Number:

UPC Number: ASP500
78378661073
Status: Active
Description:

Type ASP Aluminum Splice, Max 35KV, Wire Size 500 kcmil, Length 5 Inch, Tin Plated, Die Color Code Pink

Features

- Made of high-conductivity seamless aluminum tubing. Tin plated for corrosion resistance.
- Specifically chamfered barrel for ease of installation.
- Color-coded for matching die identification. Prefilled with oxide inhibiting compound.
- UL Listed when installed with Blackburn, Burndy, T&B or Andersons Tools.

General

Material	Aluminum
Finish	Tin Plated
Wire Size	500 kcmil
Barrel Length	Standard
Die Color	Pink

Dimension Information

Length (inches)	5
-----------------	---

Specifications

Voltage Rating	35KV
----------------	------

Tooling

Connector & Tooling Chart	Available on Website
---------------------------	----------------------

Packaging

T&B Inner Pack	2
Package in Units	20
T&B Sold in UOM	Each
T&B Weight Per UOM	43 lbs. per 100

Notes

For use with aluminum conductor (concentric, compressed or compact). Also listed for use with copper conductor.

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
Y

For further technical assistance, please contact us...

8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com