## Thomas@Betts



Pin Adapter **T&B Catalog Number:** 

PA21

**UPC Number:** 78378613405


Status: Active

**Description:** 

Aluminum Pin Adapter Terminal, Wire Size 2/0 Str, Tin Plated, Die Color Code Red

| • | , | u  | U |   | ,, | , |
|---|---|----|---|---|----|---|
| F | е | at | u | r | e  | S |

| Tin-plated stranded copper wire pigtail. Tin-plated aluminum barrel prefilled with oxide inhibitor and capped. Insulating covers included.  General |         | Connector for aluminum conductor only. Pigtail may be inserted into either aluminum or copper connectors. |
|---|---------|---|
| hibitor and capped.  Insulating covers included.  |         | Tin-plated stranded copper wire pigtail.  |
| <u> </u>  |         | '   |
| General   |         | Insulating covers included.   |
|   | General |   |



|                                | tors.   |
|--------------------------------|---|
|                                | Tin-plated stranded copper wire pigtail.            |
|                                | Tin-plated aluminum barrel prefilled with oxide in- |
|                                | hibitor and capped.                                 |
|                                | Insulating covers included.                         |
| General                        |   |
| T&B Replacement Catalog Number | 61935   |
| Material                       | Aluminum  |
| Finish                         | Tin Plated  |
| Wire Size                      | 2/0 Str.  |
| Stud Size                      | 1   |
| Barrel Length                  | Long  |
| Die Color                      | Red   |
| Dimension Information          |   |
| Outer Diameter (inches)        | .906  |
| A (inches)                     | 1 1/4   |
| B (inches)                     | 1 19/32   |
| Tooling                        |   |
| Connector & Tooling Chart      | Available on Website                                |
| Packaging                      |   |
| T&B Inner Pack                 | 10  |
| Package in Units               | 100   |
| T&B Sold in UOM                | Each  |
| T&B Weight Per UOM             | 19 lbs. per 100                                     |
| Application Support            |   |
| T&B Instruction Sheets         | ta01773-tb2   |
| Notes                          |   |
|                                | 90 Degree C rating per UL 486B                      |
| Certifications                 |   |
| RoHS Compliance                | Yes   |
| Certifications                 |   |

| T&B Instruction Sheets | ta01773-tb2                    |
|------------------------|--------------------------------|
| Notes                  |                                |
|                        | 90 Degree C rating per UL 486B |
| Certifications         |                                |
| RoHS Compliance        | Yes                            |
| Certifications         |                                |



File Nbr:

For further technical assistance, please contact us...



Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com