

ETHERLINE® 2 Pair: CAT.5/CAT.5e; Stationary

Industrial Ethernet Cable for Stationary Applications

LAPP KABEL STUTTGART ETHERLINE® CAT.5/5e

LAPP KABEL STUTTGART ETHERLINE® CAT.5e

LAPP KABEL STUTTGART ETHERLINE® CAT.5e

ETHERLINE® CAT.5/5e cables provide reliable network communication in demanding industrial environments. The high quality foil and braid shield assure protection from EMI. Cables meet the transmission requirements for Category 5 or 5e.

Recommended Applications

Stationary applications; industrial field and cell level networking; PLCs, sensors, and other network devices; dry and damp rooms; transmission rates up to 10/100 Mbit/sec

Approvals



Construction

Conductors: Solid bare copper

Pairs: 2 twisted pairs or star quad

Insulation: Polyethylene

Shielding: Foil and copper braid

Jacket: PVC; green or black – polyurethane or halogen-free; teal

Application Advantage

- Double screening ensures high transmission reliability in areas with EMI
- Flame retardant
- Highly oil- and abrasion-resistant PUR jacket
- Conforms to PROFINET® standard
- Fast connect style allows for quick installation

Cable Attributes

page 640

See attribute list by part number on page 228

Complete the Installation



Fast Connect Stripping Tool
page 257



RJ45 Connectors
page 251

ÖLFLEX® CONNECT Solution



ÖLFLEX® CONNECT CABLES
page 597

Technical Data



Minimum Bend Radius:

- for stationary use:

- 2170893: 10 x cable diameter
- 2170891: 3 x cable diameter
- 2170494: 4 x cable diameter
- 2170280, 2170281: 8 x cable diameter



Temperature Range:

- 2170893, 2170281: -40°C to +80°C
- 2170891: -40°C to +75°C
- 2170494: -25°C to +80°C
- 2170280: -30°C to +80°C



Nominal Voltage:

- (not for power applications)
- 2170893: 600V (UL AWM)
- 2170281: 1000V
- all other P/NS: 125V



Characteristic Impedance:

100Ω ± 15Ω



Color Code:

- 2170893, 2170891, 2170494: White, yellow, blue, orange
- 2170280, 2170281: White/orange & orange, white/green & green



Approvals:

- UL: AWM 21576 (2170281)
AWM 21694 (2170893)
PLTC (2170893)
CMG (2170893, 2170494)
CMX (2170891)
- Canada: c(UL) CMG (2170893, 2170494)
c(UL) CMX (2170891)
cRU AWM I/II A/B FT2 (2170281)
- Additional: RoHS

Part Number	Size / Pairs	Stranding	Jacket Material	Jacket Color	Approvals	Fast Connect	Nominal Outer Diameter (in) (mm)		Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread
CAT.5 Cable										
2170893	22 AWG/2pr	Solid	PVC	Green	PROFINET®, UL/CSA CMG, UL AWM, 600V	Yes	0.256	6.5	47	53112210
CAT.5e Cable										
2170891	22 AWG/2pr	Solid	PVC	Green	PROFINET®, UL/CSA CMX	No	0.252	6.4	38	53112210
2170494	22 AWG/2pr	Solid	PVC*	Black	PROFINET®, UL/CSA CMG	No	0.307	7.8	42	53112220
2170280	24 AWG/2pr	Solid	Halogen-free	Teal	—	No	0.229	5.8	30	53112210
2170281	24 AWG/2pr	Solid	PUR	Teal	UL/CSA AWM, 1000V	No	0.229	5.8	36	53112210

* Inner and outer jacket

PROFINET® is a registered trademark of the PNO (PROFIBUS User Organization). Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question. For current information go to our website.