

APPLICATIONS



Ideal for **7 Day** control: Lighting, signs, pumps, motors, fans, heating & air-conditioning, security systems.



FEATURES

- **AUTOMATIC INPUT VOLTAGE DETECTION**
- No DIP switch settings
- **REAL TIME** clock face
- Captive trippers
- Day/Night indication
- **4 in 1 DPDT CONTACTS** – include SPST, SPDT, DPST
- **LED INDICATORS** – Red for load status, Green for power
- 40 AMP contact
- ON/OFF/AUTO Switch

SPECIFICATIONS

INPUT VOLTAGE: 120/208-240/277VAC, 60Hz (auto detection).

TIMING ACCURACY: Line frequency.

TERMINAL RANGE: #8 - #18 AWG.

OPERATING TEMPERATURE:

-31 °F to 116 °F (-35 °C to 47 °C).

POWER CONSUMPTION: 6 watts maximum.

ENCLOSURE: Polycarbonate Indoor/Outdoor NEMA

3R or -Y suffix metal indoor NEMA 1 enclosure.

Both with lockable hasp standard



TU40
UNIVERSAL MULTI-VOLTAGE
SAME ON/OFF TIMES EACH DAY
24 HOUR TIME SWITCH

**ACCURATE
TO THE
MINUTE!**

**DETECTS INPUT
VOLTAGE
AUTOMATICALLY!**



RATINGS

NO CONTACTS:

40A Resistive @ 120-277VAC
30A Inductive @ 120-277VAC
1HP, 30FLA, 90LRA @ 120VAC
2HP, 20FLA, 60LRA @ 240VAC
30A Ballast @ 120VAC
20A Ballast @ 277VAC
15A Tungsten @ 120VAC
20A @ 28VDC
720VA Pilot Duty @ 120-240VAC
30A Max above 104 °F

NC CONTACTS:

30A Resistive @ 120-277VAC
15A Inductive @ 120-277VAC
1/4HP, 12 FLA, 30LRA @ 120VAC
1/2HP, 12FLA, 33LRA @ 240VAC
10A Ballast @ 120-277VAC
290VA Pilot Duty @ 120VAC
360VA Pilot Duty @ 240VAC