





SWITCHES

Toggle Switches: Maintained Contact Single Pole



S.P.S.T S.P.D.T
Terminal Positions

CAT. NO.	CIRCUIT FUNCTIONS	POLES & THROWS	RATINGS			ACTUATOR STYLE	ACTUATOR MATERIAL	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	H.P 125-250VAC				
78110TS	OFF-ON	SPST	6	3	—	Bat	Brass/Nickel	Screws	5
78120TQ	OFF-ON	SPST	20	10	3/4	Bat	Brass/Nickel	0.250 Quikconnect	5
78210TS	OFF-ON	SPST	20	10	3/4	Bat	Brass/Nickel	Screws	5
78200TS	ON-ON	SPDT	20	10	3/4	Bat	Brass/Nickel	Screws	5
78160TS	ON-OFF-ON	SPDT	20	10	3/4	Bat	Brass/Nickel	Screws	5
78070TQ	ON-OFF-ON	SPDT	20	10	3/4	Bat	Brass/Nickel	0.250 Quikconnect	5
Dimensions (IN) A: .687 B: .465 C: .670 D: .348 E: 1.134 F: .634 THREAD: 15/32-32UNS-2A KEYWAY: .072 X .038 DP									



S.P.S.T
Terminal Positions

CAT. NO.	CIRCUIT FUNCTIONS	POLES & THROWS	RATINGS			ACTUATOR STYLE	ACTUATOR MATERIAL	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	H.P 125-250VAC				
78150TW	ON-OFF	SPST	10*	4*	—	Bat	Brass/Nickel	Wire Leads	5
Dimensions (IN) A: .500 B: .469 C: .685 D: 1.093 E: 1.856 THREAD: 15/32-32 STANDARD 6" WIRE LEADS									

*Amperage and voltage are also valid for D.C. Rating