

APPLICATIONS



Ideal for repeating processes for poultry, livestock, agriculture, oil production, and manufacturing control.



FEATURES

- **All-in-one** control
- Easy setting with two dials
- Cycle times from **15 seconds to 24 hours**
- Percentage ON from 0% to 100%
- **960** timing combinations
- SPDT contacts provide NO and NC operation
- Load status indicated with **2-color LED**
- Suitable for harsh environments

SPECIFICATIONS

MULTI-VOLTAGE INPUT:

120 and 240VAC (+10 % -15 % at 60 Hz)

OPERATING TEMPERATURE:

32 °F to 122 °F (0 °C to 50 °C)

ENCLOSURE:

NEMA 4x Non-Metallic Indoor



EJWT DUAL VOLTAGE PERCENTAGE TIMER

UNIVERSAL
INPUT UP
TO 4!

128 EVENTS
FOR EACH DAY
OF THE WEEK!



RATINGS

NO CONTACTS:

20 A Resistive @ 120-240VAC
20 A General Purpose @ 120-240VAC
1 HP @ 120VAC
2 HP @ 208-240VAC
470VA Pilot Duty @ 120-240VAC

NC CONTACTS:

10 A Resistive @ 120-240VAC
10 A General Purpose @ 120-240VAC
1/4 HP @ 120VAC
1/2 HP @ 208-240VAC
275VA Pilot Duty @ 120-240VAC