



24-Port Gigabit GREENnet Switch

TEG-S24g (v2.0R)

- 24 Gigabit ports
- 48 Gbps switching fabric
- Fanless design
- Jumbo Frame support
- Sturdy metal switch with included rack mount brackets
- Up to 70% GREENnet energy savings*
- Limited lifetime warranty

TRENDnet's 24-Port Gigabit GREENnet Switch, model TEG-S24g, provides Gigabit performance, proven reliability, and reduced power consumption by up to 70%*. Embedded energy saving GREENnet technology works right out of the box with no management requirement. This fanless metal switch comes with rack mount brackets and offers a total switching capacity of 48 Gbps.



Plug and Play

Simply power up the switch and plug in connected devices



Ports

24 x Gigabit ports



Switching Capacity

48 Gbps switching capacity



Rack Mountable Enclosure

Fanless rack mountable 1U metal switch with include rack mount brackets



LED Indicators

LED indicators convey port status



Jumbo Frame

Sends larger packets, or Jumbo Frames (up to 10 KB), for increased performance



Energy Savings

Embedded GREENnet technology reduces power consumption by up to 70%*

Networking Solution



① LED indicators

② Gigabit ports

Specifications

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3az

Device Interface

- 24 x Gigabit Ports
- LED indicators
- On/off switch

Data Transfer Rate

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)
- Gigabit: 2000 Mbps (full duplex)

Performance

- Data RAM Buffer: 0.5 MB
- Switch Fabric: 48 Gbps
- MAC Address Table: 8 K entries
- Forwarding rate: 35.7 Mpps (64-byte packet size)
- Jumbo Frame: 10 KB

* Max power savings compared with standard TRENDnet switches.

TRENDnet offers a limited lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty

Special Features

- GREENnet energy saving technology
- Fanless
- Rack mountable

Power

- Internal power supply: 100-240 V AC, 50/60 Hz, 0.2 A
- Consumption: 13 Watts (max.)

Operating Temperature

- 0 – 40 °C (32 - 104 °F)

Operating Humidity

- Max. 90 % non-condensing

Dimensions

- 440 x 210 x 45 mm (17 x 8.3 x 1.8 in.)

Weight

- 2.3 kg (5 lbs.)

Certifications

- CE
- FCC

Warranty

- Limited lifetime warranty

Package Contents

- TEG-S24g
- Quick Installation Guide
- Power cord

