



PRODUCT CATALOGUE

ACCESSORIES



E-MAIL LICENCE FOR 1456B

E-MAIL LICENTIE VOOR 1456B

MASTER LICENCE

Code

1456B/ME1	1 MASTER LICENCE FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/ME10	10 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/ME50	50 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/ME100	100 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/ME200	200 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)

SLAVE LICENCE

Code

1456B/SE1	1 MASTER LICENCE FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/SE10	10 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/SE50	50 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/SE100	100 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/SE200	200 MASTER LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)

PHONE LICENCE

Code

1456B/TE1	1 PHONE LICENCE FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/TE10	10 PHONE LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/TE50	50 PHONE LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/TE100	100 PHONE LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)
1456B/TE200	200 PHONE LICENCES FOR 1456B, VIP SYSTEM (E-MAIL)



1456G

THIRD PARTY HOME AUTOMATION INTERFACE

Interface allowing the connection of third party Home Automation devices. 1 port for connection to part. 1440 and 4 ports for connection to the VIP monitor, and other network devices on the private network. Dimensions 70x90x62 mm (4 DIN modules).



1456S

APARTMENT SLAVE GATEWAY FOR VIP SYSTEM

Apartment gateway in slave version (requires presence of a door entry monitor). Allows the operation of door entry monitor system via tablets and smartphones using the Comelit VIP App, which can be downloaded free of charge. This function can be used locally via a Wi-Fi network or on portable devices using 3G (or higher) networks; automatic switching between Wi-Fi and 3G networks according to availability. In all cases, the gateway should be connected to an ADSL router or another device guaranteeing local Wi-Fi and mobile 3G connectivity. Depending on bandwidth limitations, the gateway can serve up to 15 appliances (including door entry monitors, smartphones, tablets and PCs) with 4 simultaneous audio/video streams. It also allows "intercom" communication between all of the 15 devices served. The gateway is equipped with 1 Ethernet port for ViP system riser input, 1 PoE port, 2 PoE ports (can be set to non-PoE) and 1 non-PoE port. It is also equipped with an input for the power supply. Dimensions: 70x90x62 mm (4 DIN modules).



1459

CALL LOG SERVER. VIP SYSTEM

Server device for ViP system that allows the recording, storage and playback of calls from external units. Complete with Call-Log administrator software for settings (IP address, date, time, enable audio, video or audio-video recording, recording duration and recording storage time) and recording filters (days of the week, external unit making the call, internal unit receiving the call). Compatible with Windows operating systems. 19 Vdc power supply. Equipped with power supply unit with 100-240 Vac 50/60 Hz input and 19 Vdc output. Dimensions: 190x190x55 mm.



1595

33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit 110-230V input and 33Vdc 500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).



1596A

POWER SUPPLY UNIT 33 VDC 60W INPUT 110-240 VAC 316 ENTR. PAN

Power supply unit with 110-230V primary and 33Vdc 1.8A continuous output for 316 range entrance panels. Equipped with internal protection against current overload and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).