



FOSC450-B6-6-NT-0-B3V | 058514-000

FOSC™450 B6 Fiber Optic Splice Closure, Gel Cable sealing, no pre-installed tray, 6 cable attach., three ground feedthrough lugs, with test valve

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Gel cable sealing technology allows easy adding or removing of a wide size range of cables
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- FOSC splice trays hinged for access to any splice without disturbing other trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments
- Compatible with CommScope's CWDM modules and optical splitter trays

Body Features

Cable Seal	Compressed Gel
Color	Black

Configuration Features

Splice Capacity	288
Port Shape	Round (6)
Flash Test Valve	Yes
Number of Pre-installed Splice Trays	none
Ground Feedthrough	Yes
Ground Feedthrough Lugs	3
Number of Cable Attachments	6
Slack Basket	Yes
Splice Capacity (Mass Fusion)	288
Splice Capacity (Single Splice, SM12 Modules)	144
Splice Capacity (Single Splice, SM6 Modules)	72

Dimensions

Closure Diameter	254.000 mm 10.000 in
Length	610.00 mm 24.02 in

Packaging Features

Minimum Order Quantity	1
Packaging Method	Box/Carton

Product Availability

Region	Latin America North America
--------	-------------------------------

Product Type Features

System	FOSC 450
Product Type	Butt Feeder & Distribution Closure

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant