Product Specifications





FOSC-450D6-6-NT-0-N-NN EH8266-000

FOSC™450 D6 Fiber Optic Splice Closure, Gel Cable sealing, no pre-installed tray, 6 cable attachments

- · Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Gel cable sealing technology allows easy adding or removing of a wide size range of cables
- · Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- FOSC splice trays hinged for access to any splice without disturbing other trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments
- Compatible with CommScope's CWDM modules and optical splitter trays

Body Features

Cable Seal Compressed Gel Color Black

Configuration Features

Port Shape Round (6) Flash Test Valve No Number of Pre-installed Splice Trays none Number of Cable Attachments 6

Dimensions

Closure Diameter 292.000 mm | 11.496 in Length 753.00 mm | 29.65 in

Packaging Features

Minimum Order Quantity Packaging Method

Box/Carton

Product Availability

Region Asia | EMEA

Product Type Features

System FOSC 450

Butt Feeder & Distribution Closure Product Type

Regulatory Compliance/Certifications

Agency Classification RoHS 2011/65/EU Compliant