

VMAX IP Plus™ 4-Channel PoE NVR with 5 Bonus Channels DW-VP9xT4P

















Dimensions Unit: Inch (mm)





Summary

The VMAX IP PLUS™ is an easy to use PoE NVR that allows you to go from power up to monitoring in less than three minutes! They support camera resolutions up to 5 Megapixels at 30fps.

eatures

- Simple and Easy to Navigate VMAX GUI for the most User-Friendly Solution on the Market
- Complete Installation, Setup and Camera Configuration in under Three Minutes!
- Control any ONVIF Camera's Setup and Features Remotely
- DW Mobile Witness™ turns a smartphone or tablet into an additional surveillance camera
- Pathfinder[™] Auto Port Forwarding
- Monitor and Record up to 9 5MP (2592x1920) Cameras (4-Channels PoE with 5 Bonus Channels)
- Local Power for up to 4 IP Cameras via Resident PoE Switch
- CCIP™ System Encryption Protects Your Surveillance System from Out of Network Attacks
- Pivot™ Remote Monitoring Software
- Mobile Application for iPhone®, iPad®, iPod®, Android® Smart Phones. and Tablets and Apple TV
- Automatic Device Discovery
- **Dual Stream Recording**
- Easy Drag and Drop Camera Management
- Instant Backup During Playback
- Full HD (1080p) Output for Local Live & Playback Display
- Complete System Analysis with Real-Time System, Network and PoE Status Monitoring
- True HD & VGA Simultaneous Output Support
- 4 Sensor Input, 1 Alarm Relay Output
- Up to 9ch Transaction Verification via TCP and USB-Serial
- Email Event Notifications with Video Clip
- Simple & Free DDNS Support for Remote Management
- Easy Web-Based Client with Multi-User Access
- Advanced H.264 Linux Embedded NVR
- Simultaneous Live, Playback, Recording, Back-up, Network
- NVR Health Check w/ Email Notification
- NVR Calculation and Auto Recording Configuration
- Help Menu on Major Functions
- Auto or Manual Firmware Upgrade Available
- Automatic Private IP Addressing
- NTP (Network Time Protocol)
- Screen Saver to Protect Monitor Screen
- Import/Export Configuration between Multiple NVRs
- USB Mouse and GUI Control
- 5 Year Limited Warranty

Available Models

- DW-VP92T4P 2TB Internal Storage DW-VP94T4P 4TB Internal Storage

866,446,3595

DW-VP93T4P - 3TB Internal Storage • DW-VP96T4P - 6TB Internal Storage







Specifications

Channel

Protocol PoE Type

Speed

Monitor

CIF

D1

1.3MF

2.1MF

Speed

Function

Firmware

Upgrade

Back Up

Special Features

Health check

5MP

Resolution

Screen Mode

No. of PoE

Communication

Operating System

System

Display

Video-In

Video-Out

Recording

Recording Resolution

Recording Modes

Playback &

Audio Output

PTZ Control

Alarm Input / Relay Output

Transaction Verification

Remote Software

Backup Device

Other Function

System Operation

Power Requirements

Power Consumption

Dimension (WxDxH)

Certification

Operating Temperature and Humidity

Search

LAN

Speed

Max. HDD Bay

Embedded Linux

100Mbps, 802.3af

IP Camera (Max. 5MP (2592x1920)

True HD Output: 800x600, 1024x768, 1280x1024,

Continuous, C+M, C+S, Scheduled, Sensor & Motion

Intelli-Search by Time Bar, Calendar (Date & Time) and

1xGigabit Ethernet (RJ45) - Fixed IP, DHCP & DDNS

Local Backup by USB, Network Backup by CMS

Pivot™, Web Client, Mobile Client for Android® & Apple®

Real-Time System, Network and PoE Status Monitoring

IR Remote Controller (Optional), USB Mouse, PTZ Control by

90.24W Total Power Budget, 1.88A, 15.4W per PoE Channel

Pre Alarm Recording, Emergency Recording,

9 channel

ONVIF®

270fps

1,489

1 x SATA HDD

1920x1080

270fps

270fps

270fps

270fps

270fps

Dual Stream

Quick Backup

Event Search

4 Ch / 1 Ch

RS-485, ONVIF

1 Ch

System Recovery after Power Failure Auto-Reboot and Journaling File System

FTP, USB

Local PoE Switch

Keyboard (Option)

41~104 °F (5~40 °C) / 20~90% RH

10.39 x 9.65 x 1.73 Inch (264 x 245 x 44 mm) CE & ECC & KCC & WEFE BoHS

48V DC

USB

Detection Recording

x1, x2, x4, x8, x16, x32

TCP and USB-Serial Interface

Smart Phones and Tablets

True HD and VGA

4 Ch

