



# 9500 Series

The strong durable, fire-rated surface mounted solution

The 9500 series is a 3 hour fire-rated, surface mounted electric strike designed to accommodate rim exit devices with a 3/4" throw Pullman latchbolt. All components are completely encased within its 3/4" thick stainless steel housing, so no cutting on the frame is required for installation. Simply place the electric strike on the surface of the frame, align it with the exit latchbolt and install. Adjustments have never been easier as the base is now separate from the cover.

The 9500 exceeds Grade 1 standards for strength and performance. It is field selectable for fail secure or fail safe operation, and for 12 or 24 VDC. This unique electric strike complies with NFPA 80-07 guidelines for retrofit into fire-rated frames.

## Specifications

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- UL 1034, burglary-resistant listed and suitable for outdoor use
- UL 294 (6th Edition) listed
- ANSI/BHMA A156.31, Grade 1
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant
- California Fire Marshall listed
- NFPA 80-07 compliant
- RoHS compliant
- Patents: 6,390,520; 8,454,063 and patent pending

## Frame Application


- Metal
- Wood

## Electrical (continuous duty)

- .45 Amps at 12 VDC
- .25 Amps at 24 VDC

## 9500 Models

9500	Universal electric strike	
RF-9500	Integrated Prox	Includes the strike body, Prox reader and door position switch
IC-9500	Integrated iCLASS®	Includes the strike body, iCLASS reader and door position switch



### Standard Features

- Installs in metal or wood frames
- Wood screws not provided
- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Tamper-resistant
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual-voltage 12 or 24 VDC
- Horizontal adjustability
- Non-handed
- Internally mounted solenoid
- Accommodates up to 3/4" Pullman latch
- Five-year limited warranty

### Optional Features

**LBM** » Latchbolt monitor

**LBSM** » Latchbolt strike monitor

### Accessories

**9000-108** » Spacer plate (black or 630 finish)

**9000-MTK** » Metal template kit

**SMB** » Surface mounting box

**2001M** » Plug-in bridge rectifier

**2004M** » ElectroLynx® adapter

**2005M3** » SMART Pac® III

**2006M** » Plug-in buzzer

### Finishes

**630** » Satin stainless steel

**605** » Bright brass

**606** » Satin brass

**612** » Satin bronze

**613** » Bronze toned

**613E** » Dark oxidized satin bronze

**629** » Bright stainless steel



RIM EXIT  
DEVICES



FIELD SELECTABLE  
(FAIL SECURE /  
FAIL SAFE)



FIELD SELECTABLE  
(12 OR 24VDC)



FIRE RATED



GRADE 1



OUTDOOR  
RATED



UL 1034  
BURGLARY  
LISTED

