

E5000 Series Electronic

Mechanical Features

- Construction: Extra heavy-duty cylindrical lockset, solid cast housings, solid cast levers, cylindrical drive wear tested for extensive use in indoor and outdoor applications
- Numeric Keypad: Vandal resistant, solid metal pushbuttons
- Door Handing: Non-handed, pre-assembled for left-hand door installations – easily changed in the field
- Standard Finishes: Satin Chrome 26D (626) housings & levers
- Backsets: 2 3/4" (70 mm), 2 3/8" (60 mm)
- Latch: 1/2" (13 mm) latch
- Minimum Stile Recommended: 5" (127 mm)
- Weight: 8 lbs. (3.63 kg)

Key Override

- Universal Key-In-Lever Cylinders: Includes Kaba 1599 6-pin cylinder (prepped to Kaba 90 or Schlage C keyway, keyed different) and tailpieces for compatibility with: Abloy 5277, Abloy 5477, Arrow C 100, ASSA 65611, ASSA 65691, Corbin Russwin 2000-03, Kaba 1539, Kaba 1599, Kaba Gemini 4730, Kaba Peaks 1099, Marks, Medeco 20W200H1, Sargent 10 Line, Schlage 23-001, Schlage Primus 20-760
- Ease of Installation: LectorBolt™ (patent pending) eliminates wiring to or through the door - no risk of pinched wires
- Door Preparation: Easily installs on wood or metal doors. ASA 161 door preparation with additional through bore holes
- Door Thickness: 1 3/8" (35 mm) to 2 1/4" (57 mm). Pre-assembled to accommodate doors 1 5/8" (41 mm) to 2" (50 mm)
- Items Supplied Include: Lock assembly, installation manual, template, quick reference guide, operations manual and required hardware
- Additional Items Supplied With Key-in-Lever Cylinder Model Only: Universal Kaba 1599 6-pin cylinder with tailpiece, two nickel silver keys

Certification and Testing

- Accessibility Standard: Americans with Disabilities Act (ADA)
- Durability: ANSI/BHMA A156.25, Grade 1 Certification
- Fire Rating: Three-hour UL/ULC fire door rating for "A" labeled doors
- Environmental: Indoor/Outdoor Approved
- Front Housing: -31° F (-35° C) to + 151° F (66° C)
- Rear Housing: -31° F (-35° C) to + 130° F (55° C)

Warranty

- Warranty: Three-year warranty from date of installation; built-in warranty counter in lock memory

Stocking Part #'s

- E5031-XK-WL-626-41 (w/key override, Kaba 90)
- E5031-B-WL-626-41 (w/key override, Best 6 or 7 pin)
- E5031-XS-WL-626-41 (w/key override, Schlage C)
- Finishes:**
Satin Chrome 626

Electronic Features

- Access Control: Electronic pushbutton lock – eliminates problems and costs associated with issuing, controlling and collecting keys and cards
- Number of Codes: 100 access codes per door; over 100 million possible code combinations
- Audit Trail: The most recent 3,000 lock events are recorded in memory including use of the mechanical key override
- Programming: Locks are programmed via keypad or with optional Microsoft Excel based software - Simplifies management of doors and users as facility's number of users and access points grow
- Operation Modes: 3 operation modes PIN access, Lockout, Passage – can be toggled on / off or can be preprogrammed to re-lock after a certain number of hours (from 1 to 24)
- Authority Levels: Five different levels allow you to control who has access to specific lock functions, includes: Service codes - programmed for one time access or "come and go" access for 1 to 24 hours
- User Parameters: Code length Adjustable to accept 4 to 8 digits
- Anti-tamper lockout Adjustable from 3 to 9 invalid attempts with an adjustable period of 0 to 90 seconds
- Re-lock time Adjustable from 2 to 20 seconds
- Battery Operation: Batteries located in interior housing cover; offers quick and easy battery replacements for institutions (Four AA Alkaline batteries provide up to 180,000 cycles) Lock data is maintained if batteries fail

