




Full size interchangeable core mortise cylinders



Cylinder Only




Compr. Ring & Spring



With Blocking Ring



Cylinders for Schlage L Series mortise locks



L & N escutcheons
(cylinders with compression ring)

All except below

30-008

20-798, 20-798-XP

30-007

L9060 outside

30-030

20-782, 20-782-XP

30-032 + 36-083

L9485, L9486 hotel functions

30-010*

N/A

30-007



Sectional trim
(cylinder with compression ring, spring and 3/8" blocking ring). 9060 requires 1/2" blocking ring.

All except below

30-138

20-776, 20-776-XP

30-137

L9060 outside

30-030 + 36-083 + 35-082-030

20-783, 20-783-XP

30-032 + 36-083 + 36-082-050

L9485, L9486 hotel functions

30-140*

N/A

30-137

* Hotel function cores are handed. Specify hand of door.




L583-255
Cam for all functions
Except L9060 outside



K510-680
Cam for
L9060 outside

Mortise cylinders with straight cam for exit devices

Number	Core mechanism	Collar
26-091	Conventional core	Compression ring & spring
20-061	Conventional core	3/8" blocking rings + compression ring & spring
20-763, 20-763-XP	Primus/Primus XP core	Compression ring & spring
20-771, 20-771-XP	Primus/Primus XP core	3/8" blocking rings + compression ring & spring
20-059	Housing less core	None
26-064	Housing less core	Compression ring & spring



K510-730
Straight cam,
other applications

- Notes
1. Available in 605, 606, 609, 612, 613, 619, 625, 626, and 643e finish. Cores furnished 606 and 626 only.
 2. To differentiate between Classic and Everest 29, specify keyway. Example: C or CP (Classic), S123 (Everest 29). Everest 29 S123 keyway standard.
 3. All cylinders are 1 1/2" long.
 4. Specify LKB if 0-bitted Primus XP cylinders are required less key blanks.