MIXER AMPLIFIER

BG-2120(CU)

IDESCRIPTION

The BG-2120 is a 120 W 5-input mixer amplifier for background music and general announcement. It is suited for use in bars, retail stores, and banquet rooms, and is equipped with the MOH OUT that permits 2-channel broadcast when used in conjunction with the optional booster amplifier BA-235 (35 W) or BA-260 (60 W).

■SPECIFICATIONS

* 0 dB = 1 V

| | * 0 db - 1 V |
|---------------------------|---|
| Power Source | 120 V AC, 60 Hz |
| Rated Output | 120 W |
| Power Consumption | 265 W (rated output), 120 W (based on cULus standards) |
| Frequency Response | 50 Hz - 20 kHz |
| Total Harmonic Distortion | |
| Input | Mic: -60 dB*, 600 Ω, electronically balanced, removable terminal block |
| | Line 1: -10 dB*/ TEL: -20 dB* |
| | Line 1/TEL selectable, 10 k Ω , electronically balanced, removable terminal block |
| | Line 2, 3: -10 dB*, 10 kΩ, unbalanced, removable terminal block and RCA jacks |
| | Module |
| Output | Speaker: 4 Ω , 25 V (5.2 Ω), 70 V (42 Ω), balanced, removable terminal block |
| | MOH: 0 dB*, 600 Ω, balanced, removable terminal block |
| | Line: 0 dB*, 600 Ω, unbalanced, removable terminal block |
| Output Regulation | 2 dB or less, no load to full load (1 kHz) |
| Phantom Power | On/Off switch for Mic, +24 V DC |
| S/N Ratio | Mic: 60 dB or more, Line 1/TEL, Line 2, 3, Module: 75 dB or more |
| | (Band Pass: 20 Hz — 20 kHz, Tone Controls: Centered) |
| Muting | Manual mute/Automatic mute |
| Tone Control | Bass: ±10 dB at 100 Hz, Treble: ±10 dB at 10 kHz |
| Control | Mic gain control, Line 1/TEL gain control, Line 2 gain control, Line 3 gain control, |
| | Module gain control, Bass tone control, Treble tone control, MOH out gain control, |
| | Mute control (Manual mute), Remote volume control, Mute sense control, |
| | Line 1/TEL selector switch, Phantom power switch (Mic), |
| | Auto mute switch (Mic, Line 1/TEL, Module), |
| | Mute receive switch (Mic, Line 1/TEL, Line 2, 3, Module), |
| | MOH assign switch (Mic, Line 1/TEL, Line 2, 3, Module), Power ON/OFF switch |
| Indicator | Power LED, Signal level LED, Peak LED |
| Operating temperature | 0 °C to +40 °C (32 °F to 104 °F) |
| Operating Humidity | 35 % to 80 %RH (no condensation) |
| Finish | Panel: ABS resin, black |
| | Case: Steel plate, black, paint |
| Dimensions | 264 (W) × 94.3 (H) × 267.3 (D) mm (10.39" × 3.71" × 10.52") |
| Weight | 6 kg (13.23 lb) |
| Accessory | Volume control cover: YA-9205, Removable terminal plug (2 pins)4, |
| | Removable terminal plug (3 pins)2, Removable terminal plug (4 pins)1, |
| | Removable terminal plug (5 pins)1 |
| Option | Rack mounting bracket: MB-1000 |

■ APPEARANCE

