



Model TS-14

Pneumatic Mushroom Push Button

Specifications

- Contacts rated 10A at 120 VDC
- Switch depth behind plate: 2-1/2"
- 10" color coded leads
- One normally-open and one normally-closed contact
- Timer life: one million operations

Options

- Order TS-14R or TS-14NR for red button
- TS-14N and TS-14NR are mounted on narrow 1-3/4" 302 stainless satin steel wall plate
- Other wall plate finishes available
- Custom silkscreening is available

Features

- Switch mounted on single gang 430 stainless steel wall plate
- TS-14 and TS-14N have a green button standard
- Requires no external power
- Labeled "PUSH TO EXIT"
- Adjustable time range 2 to 60 seconds

Models

TS-14

Pneumatic Time Delay, 1 N/O & 1 N/C Contact, 1-1/2" Diameter Green Push Button, "PUSH TO EXIT", Single Gang, Stainless Steel Plate

TS-14R

Pneumatic Time Delay, 1 N/O & 1 N/C Contact, 1-1/2" Diameter Red Push Button, "PUSH TO EXIT", Single Gang, Stainless Steel Plate

TS-14NR

Same as TS-14N Except Red Push Button

TS-14N

Same as TS-14 Except Mounted on 1-3/4" Satin Stainless Steel Plate

ALARMCONTROLS



ASSA ABLOY