

Double-Door Electromagnetic Locks

- E-941DA-600Q** 600-lb Holding Forcer per door, UL Listed
- E-941DA-600PQ** 600-lb Holding Force per door, with Bond Sensors, LEDs, UL Listed
- E-941DA-1K2Q** 1,200-lb Holding Force per door, UL Listed
- E-941DA-1K2P** 1,200-lb Holding Force per door, with Bond Sensors, LEDs, UL Listed

Features:

- Anodized aluminum housing (US 28)
- 12 or 24VDC (selectable)
- No residual magnetism
- MOV surge protection
- Adjustable mounting bracket
- Complete mounting hardware for typical installations
- "L" bracket and "Z" brackets available for easy mounting
- Detachable faceplate.



E-941DA-600Q
(shown)

Magnet Dimensions:
19^{11/16}" x 1^{5/8}" x 1"
(500 x 42 x 25 mm)

E-941DA-600PQ and E-941DA-1K2P feature:

- Built-in dual-colored status LEDs and bond sensors to show locking status of each door

Green	Door is closed and locked
Red	Door not closed and/or locked
Off	Door in use / No power

- Bond sensor relay: 3A@12VDC



E-941DA-1K2P
(shown)

Magnet Dimensions:
21" x 2^{5/8}" x 1^{5/8}"
(536 x 67 x 42 mm)

Specifications:

		DA-600Q	DA-600PQ	DA-1K2Q	DA-1K2P
Holding force (per door)		600-lb (272kg)		1,200-lb (545kg)	
Operating Voltage		12 or 24 VDC ±10%			
Current Draw	12VDC	500mA			
	24VDC	250mA			
Bond sensor relay		3A@12VDC			
Operating temperature		14°~131° F (-10°~55° C)			
Weight		9-lb (4kg)		21-lb (10kg)	
Bond Sensor relay			•		•
Status LEDs			•		•

Complete line of "Z", "L" and specialty mounting brackets available:



E-941S-1K2/ZQ
(shown)

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com | Email: sales@seco-larm.com



Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI

Pi-E-941-DA_151007.docx