



## ELOCK-FA CIRCUIT LOCKOUT KIT



- Circuit lockout tab
- Hex key
- Breaker, legend, and door labels

## NFPA 2013 CODE COMPLIANCE

- 10.6.5.2 Circuit Identification and Accessibility.
  - 10.6.5.2.1 The location of the branch circuit disconnecting means shall be permanently identified at the control unit.
  - 10.6.5.2.2 System circuit disconnecting means shall be permanently identified as to its purpose in accordance with the following:
    - (1) "FIRE ALARM" for fire alarm systems
    - (2) "EMERGENCY COMMUNICATIONS" for emergency communications systems
    - (3) "FIRE ALARM/ECS" for combination fire alarm and emergency communications systems
  - 10.6.5.2.3 For fire alarm and/or signaling systems, the circuit disconnecting means shall have a red marking.
  - 10.6.5.2.4 The red marking shall not damage the overcurrent protective devices or obscure the manufacturer's markings.
  - 10.6.5.2.5 The circuit disconnecting means shall be accessible only to authorized personnel.
- 10.6.5.3 Mechanical Protection. The branch circuit(s) and connections shall be protected against physical damage.
- 10.6.5.4 Circuit Breaker Lock. Where a circuit breaker is the disconnecting means, a listed breaker locking device shall be installed.



toll free 1.800.486.1723 | fax 508.485.4740

© Copyright 2015 Space Age Electronics, Inc. | This document is subject to change without notice | SS10101 | Rev. 1



1SAE.COM Pg. 1/1

