

## General Information

<b>Extended Product Type:</b>	CM-PVE
<b>Product ID:</b>	1SVR550871R9500
<b>EAN:</b>	4013614348112
<b>Catalog Description:</b>	CM-PVE Phase monitoring relay 1n/o, L1,2,3=320-460VAC
<b>Long Description:</b>	Phase monitoring relay CM-PVE, width 22.5mm, monitoring of single- or three phase over- and undervoltage, phase loss, measuring range L1-L2-L3=320-460VAC, powered by measuring circuit, 1 n/o (closed circuit principle)

## Additional Information

<b>CB Certificate:</b>	CB_DK-8880
<b>CCC Certificate:</b>	CCC_2013010303605960
<b>Country of Origin:</b>	Bulgaria (BG)
<b>Customs Tariff Number:</b>	85364900
<b>Data Sheet, Technical Information:</b>	2CDC112190D0201
<b>Declaration of Conformity - CE:</b>	1SVD981025-0001
<b>EAC Certificate:</b>	EAC_RU_C-BG.ME77.B.00507
<b>EAN:</b>	4013614348112
<b>EPLAN Catalog Tree:</b>	Electrical engineering / Relays, contactors / General
<b>ETIM 4:</b>	EC001441 - Phase monitoring relay
<b>ETIM 5:</b>	EC001441 - Phase monitoring relay
<b>ETIM 6:</b>	EC001441 - Phase monitoring relay
<b>Environmental Information:</b>	1SAA981003-2403
<b>Function:</b>	Phase failure detection Over- and undervoltage monitoring
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SVC550510M0001
<b>Invoice Description:</b>	CM-PVE Phase monitoring relay 1n/o, L1,2,3=320-460VAC
<b>Measurement Threshold:</b>	Fixed
<b>Measuring Range:</b>	(L-L) 320 ... 460 V AC
<b>Minimum Order Quantity:</b>	1 piece
<b>Object Classification Code:</b>	B
<b>Output:</b>	1 n/o contact
<b>Package Level 1 EAN:</b>	4013614348112
<b>Package Level 1 Gross Weight:</b>	0.078 kg
<b>Package Level 1 Height:</b>	83 mm
<b>Package Level 1 Length:</b>	25 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	24 mm
<b>Power Loss:</b>	Approximately 2 W
<b>Product Main Type:</b>	CM-PVE
<b>Product Name:</b>	Three-Phase Monitoring Relay
<b>Product Net Depth:</b>	78.5 mm
<b>Product Net Height:</b>	78 mm
<b>Product Net Weight:</b>	0.066 kg
<b>Product Net Width:</b>	22.5 mm

Product Reference:	22.01111
RMRS Certificate:	RMRS_1740020250
Rated Control Supply Voltage (U <sub>s</sub> ):	(L-L) 320 ... 460 V AC
Rated Frequency (f):	Supply Circuit 50/60 Hz
Regulatory Compliance Mark (RCM):	Yes
RoHS Date:	1146
RoHS Information:	1SVD981025-0001
RoHS Status:	Following EU Directive 2011/65/EC
Selling Unit of Measure:	piece
Short Description:	CM-PVE Phase monitoring relay
Standards:	EN 50178 EN 50581 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508 CAN/CSA C22.2 No.14
Sub-Function:	Phase loss
Sub-Function 2:	02 Over- and undervoltage (fixed)
Sub-Function 3:	Over- and undervoltage (fixed)
Terminal Type:	Screw Terminals
Time Range:	500 ms start-up delay 500 ms tripping delay
UL Certificate:	UL508_E140448
UNSPSC:	39121500
cUL Certificate:	cUL508_E140448
eClass:	7.0 27371803