

**190SE****Fixed-tuned CPR90G for elliptical waveguide 90**

General Specifications

Body Style	Straight, fixed-tuned
Interface	CPR90G
Waveguide Size	WR90 WG16 R100
Brand	HELIAX®
Material Type	Brass

Electrical Specifications

Operating Frequency Band	10.2 – 11.7 GHz
Insertion Loss, typical	0.01 dB
Peak Power, maximum	44.90 kW @ 11.20 GHz

Mechanical Specifications

Attachment Method	Tab-flare Tool-flare
Inner Contact Plating	Unplated
Outer Contact Plating	Unplated
Pressurizable	Yes

Dimensions

Length	80.77 mm 3.18 in
Transition Length	46.23 mm 1.82 in
Weight	1.00 kg 2.20 lb
Width	72.39 mm 2.85 in

Environmental Specifications

Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-55 °C to +85 °C (-67 °F to +185 °F)

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

190SE



* Footnotes

Insertion Loss, typical 0.05v⁻freq (GHz) (not applicable for elliptical waveguide)