



FPCA-MMYP003M | 300001763596

Fiber Optic Patch Cord, singlemode, 1.2 mm OFNP jacket, LC/APC-LC/APC, 3 m, yellow

- 1.2 mm diameter cable provides a 65% space savings over commonly used 2.0 mm cable
- 1.2 mm diameter fiber patch cords use Reduced Bend Radius (RBR) fiber cable
- Typically used in environments where space constraints and cable routing prove most challenging

Product Classification

| | |
|-----------------------|-------------------------------|
| Product Type | Fiber patch cord, simplex |
| Regional Availability | Latin America North America |
| Product Series | FPCA |

Body Features

| | |
|-------------------------|-------|
| Connector Color (End A) | Green |
| Connector Color (End B) | Green |

Configuration Features

| | |
|------------------------------|---|
| Number of Connectors (End A) | 1 |
| Number of Connectors (End B) | 1 |

Construction Materials

| | |
|------------------------|--------|
| Jacket Color | Yellow |
| Total Fibers, quantity | 1 |

Dimensions

| | |
|----------------------|------------------|
| Assembly Length | 3.00 m 9.84 ft |
| Cable Outer Diameter | 1.2 mm |

Industry Standards

| | |
|---------------------|--|
| Approved Standards | GR-326 CORE GR-409 GR-449-CORE IEC 61754-4 TIA-604-3-B |
| Flammability Rating | OFNP (Plenum) Jacket |

Product Type Features

| | |
|-------------------------|-----------------|
| Connector Type (End A) | LC/APC |
| Connector Type (End B) | LC/APC |
| Fiber Type | OS1 |
| Fiber Diameter | 9/125 μ m |
| Connector Style (End A) | Simplex |
| Connector Style (End B) | Simplex |
| Fiber Cable Type | Duplex, dualzip |
| Optical Mode | Singlemode |

FPCA-WMYP003M | 300001763596

Signal Characteristics

| | |
|----------------------|---------|
| Insertion Loss (Max) | 0.40 dB |
| Return Loss (Min) | -65 dB |

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant

* Footnotes

Assembly Length Assembly length includes the breakout lengths