



L4A-BDFDR-6-P
LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Female Bulkhead and 7-16 DIN Male Right Angle , 6FT

General Specifications

| | |
|--------------------------------------|--------------------|
| Body Style, Connector A | Bulkhead |
| Body Style, Connector B | Right angle |
| Cable Family | LDF4-50A |
| Interface, Connector A | 7-16 DIN Female |
| Interface, Connector B | 7-16 DIN Male |
| Nominal Size | 1/2 in |
| Length | 1.829 m 6.000 ft |
| Specification Sheet Revision Level B | |

Electrical Specifications

| | |
|----------------------------------|---------------------------|
| 3rd Order IMD Static | -159.00 dBc -116.00 dBm |
| 3rd Order IMD Static Test Method | Two +43 dBm carriers |
| DTF, Connector A | -34.00 dB |
| DTF, Connector B | -30.00 dB |

Jumper Assembly Sample Label



Return Loss/VSWR

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|------|------------------|
| 698–960 MHz | 1.08 | 28.00 |
| 1700–2200 MHz | 1.08 | 28.00 |
| 2200–2700 MHz | 1.13 | 24.00 |

Regulatory Compliance/Certifications

| Agency | Classification |
|--------|----------------|
|--------|----------------|

L4A-BDFDR-6P

RoHS 2011/65/EU
China RoHS SJ/T 11364-2006



Included Products

LDF4-50A — LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket

CX-10D-SA — HELIAX® Low Density Foam Coaxial Cable, corrugated copper, black PE jacket, special marking "SWCC
SHOWA CX-10D-SA ANDREW HELIAX® 1/2" LDF4-50A"

LDF4-50A-2T — LDF4-50A-2T, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket

12L450 — 1/2", HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket