



L4A-DMDM-10M-P

**LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male, 10 m**

## General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Cable Family	LDF4-50A
Interface, Connector A	7-16 DIN Male
Interface, Connector B	7-16 DIN Male
Nominal Size	1/2 in
Length	10.000 m   32.808 ft
Specification Sheet Revision Level	B

## Electrical Specifications

3rd Order IMD Static	-159.00 dBc   -116.00 dBm
3rd Order IMD Static Test Method	Two +43 dBm carriers
DTF, Connector A	-34.00 dB
DTF, Connector B	-34.00 dB

## Jumper Assembly Sample Label



## Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.10	26.40
1700–2200 MHz	1.10	26.40
2200–2700 MHz	1.13	24.00

L4A-DMDM-10M-P

## Regulatory Compliance/Certifications

### Agency

ISO 9001:2008

### Classification

Designed, manufactured and/or distributed under this quality management system

## Included Products

LDF4-50A — LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket

L4XDM-DT — 7-16 DIN Male for 1/2 in LDF4-50A cable, factory attached

L4XDM-TU — 7-16 DIN Male for 1/2 in LDF4-50A cable, factory attached

L4DM-S2 — 7-16 DIN Male for 1/2 in LDF4-50A cable, factory attached

L4KM-S2 — 4.1/9.5 DIN Male for 1/2 in LDF4-50A cable, factory attached

LDF4-50A-2T — LDF4-50A-2T, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket

12L450 — 1/2", HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket