

BREAKER BQD 3P 45A 480VAC 14KA



|                                               |                             |
|-----------------------------------------------|-----------------------------|
| Number of poles                               | 3                           |
| Suitability for operation                     | CONSTRUCTION                |
| Electricity                                   |                             |
| Continuous current rated value                | 45 A                        |
| Supply voltage frequency rated value 50/60 Hz | Yes                         |
| Environmental conditions                      |                             |
| Ambient temperature during operation maximum  | 40 °C                       |
| Model                                         |                             |
| product brandname                             | SIEMENS                     |
| Special product feature                       | PANELBOARD MOUNT            |
| Type of electrical connection                 | LOW TAB                     |
| Mechanical Design                             |                             |
| Depth [in]                                    | 4 in                        |
| Design of the overload release                | THERMAL MAGNETIC TRIP UNIT  |
| Design of the product                         | BQD                         |
| Height [in]                                   | 3 in                        |
| Material of the enclosure                     | MOLDED CASE CIRCUIT BREAKER |
| Size of the circuit-breaker                   | 100A                        |

|                          |                  |
|--------------------------|------------------|
| Width [in]               | 3 in             |
| General product approval |                  |
| Standard                 | UL 489 CSA-C22.2 |
| last modified:           | 08/20/2017       |