

Keyspan Mini DisplayPort 1.2 to HDMI 2.0 Active Adapter/Video Converter (M/F), Thunderbolt 1 & 2 Compatible, 4K x 2K @ 60Hz, HDMI 2.0, HDCP 2.2, 6 in.

MODEL NUMBER: **P137-06N-H2V2**



Description

The P137-06N-H2V2 Keyspan® Mini DisplayPort 1.2 to HDMI 2.0 Active Adapter and Video Converter (M/F) connects a PC or Mac with a Mini DisplayPort or Thunderbolt 1 & 2 output port to the HDMI input port on a 4K-enabled monitor, projector or television. Devices supported include Chromebooks, MacBooks, Microsoft Surfaces and other computers and laptops equipped with mDP or Thunderbolt ports.

This unit lets you use your existing HDMI display instead of buying a new mDP monitor. Compliant with HDMI 2.0 specifications, it is ideal for displaying crystal-clear video on a large monitor or digital sign. It supports Ultra High Definition (UHD) video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz, as well as HDCP 2.2. It also supports audio signals as long as the mDP source does (check your source's manual for compatibility).

The active adapter converts both Single-Mode and Dual-Mode (DP++) DisplayPort output. It's recommended for use with graphics cards, such as AMD Eyefinity, that do not output DP++ signals.

The P137-06N-H2V2 is plug-and-play with no software, drivers or power supply needed. Nickel-plated connectors and gold-plated contacts ensure excellent conductivity. Integral strain relief ensures the converter and molded connectors last a long time. The P137-06N-H2V2 fits easily in a briefcase, backpack or laptop bag for connecting on the go.

Features

Sends Mini DisplayPort 1.2 Audio/Video to an HDMI Display

- Connects PC or Mac's mDP or Thunderbolt 1 & 2 output to HDMI-enabled monitor, projector or TV
- Ideal for displaying video on large monitor or digital sign

Vibrant Video Quality

Highlights

- Complies with mDP and Thunderbolt™ 1 & 2 ports on PCs and Macs
- Supports video resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports audio and HDCP 2.2
- Converts both Single-Mode and Dual-Mode mDP output
- Complies with HDMI 2.0 specifications

System Requirements

- PC or Mac with mDP or Thunderbolt 1 & 2 output
- Display with HDMI input
- Both display and source must support 4K x 2K @ 60 Hz to display 4K x 2K video
- Audio supported as long as source does. Check source manual for compatibility.

Package Includes

- P137-06N-H2V2 Keyspan Mini DisplayPort 1.2 to HDMI 2.0 Active Adapter (M/F), 6 in.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

- Complies with HDMI 2.0 specifications
- Supports UHD video resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports audio and HDCP 2.2
- Converts both Single-Mode and Dual-Mode DisplayPort output
- Works with graphics cards that don't output DP++ signals

Superior Materials for Superior Performance

- Nickel-plated connectors and gold-plated contacts for excellent conductivity
- Integral strain relief for long life
- Plug-and-play—no software, drivers or power supply necessary
- Fits easily into briefcase, backpack or laptop bag

Specifications

INPUT	
Cable Length (ft.)	0.5
Cable Length (m)	0.2
Cable Length (in.)	6
Cable Length (cm)	15.24
PHYSICAL	
Color	White
CONNECTIONS	
Side A - Connector 1	MINI DISPLAYPORT (MALE)
Side B - Connector 1	HDMI (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>