

High Security Tubular Key Locks GEM 1000 Series Locks

7 Pin Tumbler





		T					B
Illustration	Number	Description					Box Qty.
Cam Locks - Nickel Plated - Featuring FlexaCam! KD, KA 27379, 27380, 27381, 27382, 27383, 27384, 27385							
	• Multi-function						
	MFW1038	1/2" 'A' Dimension (Not Available Master Keyed)					25
	MFW1058	23/32" 'A' Dimension					25
	MFW1078	15/16" 'A' Dimension					25
	MFW1118	1- 5/32" 'A' Dimension					25
	MFW1148	1-1/2" 'A' Dimension (Not Available Master Keyed)					25
Switch Lock - Momentary & Maintaining - Nickel KD, KA 27379, 27380, 27381, 27382, 27383							
	 Multi-function 						
	MFSW3-1138	Rekeyable Switch Lock - UL Rated Maintaining & Momentary Contact, Single Pole, Double Throw Switch, 125/250VAC 7A (Resistive Load) Lead Length 10" 'A' Dimension 1-3/8"	Parts Provided For:				
			Function	Turn	Key Removable	Function	10
			1	90° CW	12 & 3	Maintained	
			2	90° CW	12	Momentary	
						Spring Back	
Curitals Locals Maintaining Nielsel District							
Switch Lock - Maintaining - Nickel Plated KD, KA 27379, 27380, 27381, 27382, 27383							
	Multi-function	Multi-function					
	SW2-1138AD	Maintains Contact at 3:00 Single Pole, Single Throw Switch 7 Amps @ 28 VAC/VDC Key Removable At 12:00 & 3:00 'A' Dimension, 1-3/8" Lead Length 10"					10
		I					
Switch Lock - Momentary - Nickel Plated KD, KA 27379, 27380, 27381, 27382, 27383							
	• Multi-function						
A A A A A A A A A A A A A A A A A A A	SW20-1138MC	Momentary Contact, Single Pole, Single Throw Switch 7 Amps @ 28 VAC/VDC Operation: 90° CW Turn Contacts Closed - Spring Back to 12:00, Key Removable 'A' Dimension, 1-3/8" Lead Length 10"					10