


5236-5246 SERIES SWITCH CONSOLES


5246 SERIES









5236 SERIES







SPECS:

SWITCH RATING: 3A @ 115VAC OR 28VDC UL RECOGNIZED/CSA CERTIFIED

OPERATING TEMP: +5F to +158F

L.E.D. RATING: .02A @24VDC

ENCLOSURE: ANODIZED ALUMINUM


KEY SWITCHES

SPDT K24

(1 SET OF CONTACTS SHOWN) <u>l yellow</u> n.c. GRAY CDM. TRANGE N.D.




DPDT- K331/332




PUSH BUTTONS


SPDT P15



DPDT-P25



L.E.D. OPTION



Example Model Descriptions

5236-P15 = 1 SPDT Push Button mounted on 2-1/2 x 2 x 1" Box 5236-2P15 = 2 SPDT Push Buttons mounted on 2-1/2 x 2 x 1" Box

5246-K24xP15 = 1 SPDT Key Switch 1 SPDT Push Button mounted on a 3-3/4 x 2-1/2 x 1-1/2" Mini Box Console Kev removable in 2 positions

5246-K331xP15 = 1 DPDT Key Switch 1 SPDT Push Button mounted on a 3-3/4 x 2-1/2 x 1-1/2" Mini Box Console Key removable in 1 position

5246-K332xP15 = 1 DPDT Key Switch 1 SPDT Push Button mounted on a 3-3/4 x 2-1/2 x 1-1/2" Mini Box Console Key removable in 2 positions

Options

Any combination of Push Buttons and LED's may be utilized. Up to 4 on the 5236 series. Up to 4 on the 5246 series

xL = Optional Single Red/Green LED.

xL2 = Two Optional Red/Green LEDs.

xL3 = Three Optional Red/Green LEDs.

xP15 = Optional Momentary SPDT Push

x2P15 = Two Optional Momentary SPDTPush Buttons.

x3P15 = Three Momentary SPDT Push **Buttons**

x4P15 = Four Momentary SPDT PushButtons.

xP25 = Optional Momentary DPDT Push Button

Electrical Specifications

Key Switch Contacts -Rated 3 amps @ 125 VAC or 28 VDC. UL RECOGNIZED/CSA CERTIFIED

Push Button Switch Contacts - Rated 3 amps @ 125 VAC or 28 VDC. UL RECOGNIZED/CSA CERTIFIED

LED - Red/Green Bi-polar - 12/24 VDC. .02 amps @24vdc

MINI BOX -Clear Anodized Aluminum Housing 1/8" thick Cover 3/64" thick

Distributed by: