




Full size interchangeable core mortise cylinders



Cylinder Only



Compr. Ring & Spring



With Blocking Ring



Cylinders for Schlage L Series mortise locks



L & N escutcheons (cylinders with compression ring)

All except below	30-008	20-798, 20-798-XP	30-007
L9060 outside	30-030	20-782, 20-782-XP	30-032 + 36-083
L9485, L9486 hotel functions	30-010*	N/A	30-007



Sectional trim (cylinder with compression ring, spring and 3/8" blocking ring). 9060 requires 1/2" blocking ring.

All except below	30-138	20-776, 20-776-XP	30-137
L9060 outside	30-030 + 36-083 + 35-082-030	20-783, 20-783-XP	30-032 + 36-083 + 36-082-050
L9485, L9486 hotel functions	30-140*	N/A	30-137

Core mechanism

Conventional

Primus, Primus XP

Housing less core



L583-255
Cam for all functions
Except L9060 outside




K510-680
Cam for
L9060 outside

* Hotel function cores are handed. Specify hand of door.

Mortise cylinders with straight cam for exit devices

Number	Core mechanism	Collar
26-091	Conventional core	Compression ring & spring
20-061	Conventional core	3/8" blocking rings + compression ring & spring
20-763, 20-763-XP	Primus/Primus XP core	Compression ring & spring
20-771, 20-771-XP	Primus/Primus XP core	3/8" blocking rings + compression ring & spring
20-059	Housing less core	None
26-064	Housing less core	Compression ring & spring



K510-730
Straight cam,
other applications

- Notes
1. Available in 605, 606, 609, 612, 613, 619, 625, 626, and 643e finish. Cores furnished 606 and 626 only.
 2. To differentiate between Classic and Everest 29, specify keyway. Example: C or CP (Classic), S123 (Everest 29). Everest 29 S123 keyway standard.
 3. All cylinders are 1 1/2" long.
 4. Specify LKB if 0-bitted Primus XP cylinders are required less key blanks.