



M62FG-SASM

1,200 lbs Holding Force Gate Magnalock®

The Shock Absorbing Magnalock Solution for Outdoor Gates

The M62FG-SASM is the only heavy duty Magnalock specifically designed to secure and protect gates. This weatherproof unit delivers 1,200 lbs of holding force and comes equipped with conduit fittings and a special shock absorbing strike mount (SASM). This unique design dramatically prolongs the life of the lock, the gate and other hardware by controlling excessive impact between the strike plate and the magnet.

The SASM is also available as a separate retrofit kit and is compatible with M32, M62 or M82 Magnalock strike plates for areas prone to excessive force closures or slamming.

PRODUCT FEATURES

- Flexible bracket options for swinging or sliding applications
- Fully sealed for weather-proof operations
- Includes universal threaded conduit fitting 1/2" female - 3/4" male
- 10 ft. [3.05m] of jacketed, stranded conductor cable
- Noise suppression with included MOV
- Automatic dual-voltage - no field adjustment required
- Rust resistant - all ferrous metal surfaces plated for durability
- MagnaCare® lifetime replacement, no fault warranty

PRODUCT OPTIONS

- (B) BondSTAT™ magnetic bond sensor - Patented (MBS)
- (D) Integrated door position switch (DPS)
- (F) Face drilled
- (G) Gate conduit
- (SASM) Shock absorbing strike mount - shock absorption and rebound assistance for proper gate alignment

SPECIFICATIONS

- UL 10C Listed
- CAN4-S104, CAN/ULC-S533 Listed
- ANSI/UL 294 Listed
- CSA-C22.2 No.205 Listed
- ANSI/BHMA A156.23, Grade 1; E08501-1000
- CSFM - California State Fire Marshal Approved
- MEA - City of New York Approved
- Patent: 8,094,017

Holding Force:

1,200 lbs [544kg]

Dimensions:

8"L x 1-3/4"D x 3"H

Electrical:

250 mA at 12 VDC
150 mA at 24 VDC

Operating Temperature:


-40 to +140F [-40 to +60C]
Indoor or outdoor use

Shipping Weight:

12 lbs [5.44kg]

Finishes:

US32D/630 - Satin Stainless Steel



M62FG-SASM on Swinging Gate Using Flex-Mount Bracket Kit FMK-SW



M62FG-SASM on Sliding Gate Using Flex-Mount Bracket Kit FMK-SL



MODELS

PART # | Description

M62FG-SASM	M62 Magnalock- 12/24 VDC, Face Drilled, Gate Conduit w/SASM Bracket
M62FG	M62 Magnalock- 12/24 VDC, Face Drilled, Gate Conduit
M62FGB	M62 Magnalock- 12/24 VDC, Face Drilled, Gate Conduit, MBS
M62FGBD	M62 Magnalock- 12/24 VDC, Face Drilled, Gate Conduit, MBS, DPS
M62FGD	M62 Magnalock- 12/24 VDC, Face Drilled, Gate Conduit, DPS
SASM	Shock Absorbing Strike Mount for M32, M62, M82

For flexible mounting brackets, see page 39.



DUAL VOLTAGE



GRADE 1



FIRE RATED

SECURITRON
ASSA ABLOY