

MODEL	DESCRIPTION
LC-100	External unit that operates on 11 through 29 AC/DC input and provides inductive kickback and surge protection. When used with the EN Series, 12DC must be selected and the LC100 must be located within 10' of the electric strike.
EN-CA-12DC	Coil Assembly (Orange/White Wire Leads)
EN-CA-24DC	Coil Assembly (Black/White Wire Leads)
EN-CA-12AC	Coil Assembly (Blue/Orange & White Wire Leads)
EN-CA-24AC	Coil Assembly (Blue/Black & White Wire Leads)
EN-SLR-RS	(1) Fail Safe Slider for 430/435 Units
TRS	(2) Tamper-Resistant Torx® #12-24 Screws
EN-TS	Trim Skirt (Not for use with 950 & 960)
EN-LSK	EN Latch Shim Kit for horizontal cavity adjustment.
ESK-1	EN Service Kit: <ul style="list-style-type: none"> <li>• (1) Latch spring</li> <li>• (2) PFH 12-24x1" mounting screws &amp; (2) PFH 6-32 x 1/8" cover screws</li> <li>• (2) Wire nut caps &amp; (1) assembly pin and instruction sheet</li> </ul>
BZ-12	Buzzer for 12 DC operation
BZ-24	Buzzer for 24 DC operation
EN400-Gatebox	The weldable gate box solution for use with the EN400 & EN400RP Outdoor rated electric strikes. (Steel gatebox is <u>Not Finished</u> ).

**EN400-Gatebox  
Dimensions**

