

Light Commercial Electric Strikes

00 Series

Light
Commercial Strikes



005

For use in replacement installations in wood jambs and iron gates. Use with bored cylindrical locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 3-1/2" x 1-3/8" – Mortise Backset 2-3/4" – Cavity Depth 1/2" – Cavity Width 9/16" – Cavity Height 1-1/2"

005
(Brass Powder Coated)
005C
(Satin Chrome – BHMA651)
RS (Fail Safe)
- For DC Models only.



HD005

Screwed-on Faceplate and reinforced Latch Pin provide additional strength for HEAVY DUTY installations.

For use in replacement installations in wood jambs and iron gates. Use with bored cylindrical locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 3-1/2" x 1-3/8" – Mortise Backset 2-3/4" – Cavity Depth 1/2" – Cavity Width 9/16" – Cavity Height 1-1/2"

HD005
(Brass Powder Coated)
HD005C
(Satin Chrome – BHMA651)
RS (Fail Safe)
- For DC Models only.



S005

For use in replacement installations in wood jambs and iron gates. Use with bored cylindrical locksets having up to 3/4" throw, based on 1/8" door gap.

Face Plate 3-1/2" x 1-3/8" – Mortise Backset 2-7/8" – Cavity Depth 5/8" – Cavity Width 23/32" – Cavity Height 1-1/2"

S005
(Brass Powder Coated)
S005C
(Satin Chrome – BHMA651)
RS (Fail Safe)
- For DC Models only.



006

For surface mount installations on metal or wood jambs, for in swinging applications. Use with locksets or night latches having up to 5/8" throw, based on 1/8" door gap. When mounted on a pair of doors, strike is mounted to the inactive leaf.

Case 2-1/8" x 1-3/16" – Surface Mounted – Die Cast Housing – Cavity Depth 1/2" – Cavity Width 1/2" – Cavity Height 1-3/8"

006
(Brass Powder Coated)
RS (Fail Safe)
- For DC Models only.



007

For use in new or replacement installations in wood jambs. Use with locksets having up to 3/4" throw, based on 1/8" door gap.

Face Plate 4-7/8" x 1-1/4" – Mortise Backset 2-7/8" – Cavity Depth 5/8" – Cavity Width 3/4" – Cavity Height 1-1/2"

007
(Brass Powder Coated)
007C
(Satin Chrome – BHMA651)
RS (Fail Safe)
- For DC Models only.