

760221697 | PNL-CS-24LCX-PT
LazrSPEED® Splicing cassette, 24LC, 900µm



Construction Materials

Fiber Type	LazrSPEED® 550, 50 µm multimode fiber (OM4)
Total Fibers, quantity	24

Dimensions

Depth	165.35 mm 6.51 in
Height	28.96 mm 1.14 in
Pigtail Length	1.5 m 4.9 ft
Width	104.65 mm 4.12 in

Environmental Specifications

Safety Standard	UL
-----------------	----

General Specifications

Brand	CommScope®
Product Type	Cassette
Interface, front	LC
Adapter Color	Aqua
Interface Feature, front	Standard
Package Quantity	1
Total Ports, quantity, front	12

Optical Performance

Insertion Loss Change, mating	0.30 dB
Insertion Loss Change, temperature	0.30 dB
Insertion Loss, typical	0.30 dB
Return Loss, minimum	25.0 dB

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	
ISO 9001:2008	

* Footnotes

Insertion Loss Change, mating	Maximum insertion loss change after 500 matings
Insertion Loss Change, temperature	Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)