



ADVANCED
TECHNOLOGY
VIDEO

VALUE LINE SERIES

>>> REAL TIME 960H, FULL HD, MULTI-CHANNEL DIGITAL RECORDERS



960H, H.264 DVR

VLD904 / VLD908 / VLD916

- > Available in Models with 4, 8, or 16 Channels of Video
- > H.264 Compression with Real Time 30-FPS/Channel at 960H Resolution
- > Full High Definition (Full HD), 1920 x 1080 Display with HDMI or VGA Monitors Simultaneously
- > P2P (Point to Point) Easy Network Connectivity
- > Event and Alarm Notifications through CMS or Email Server
- > Programmable Video Motion Detection, Alarm In and Video Loss Alarm Inputs by Camera
- > PTZ Camera Control Via RS-485 Connection
- > IR Remote Control and USB Mouse Included
- > Mobile Remote Monitoring App with Android, iPhone and iPad devices
- > 4 channels of Audio Recording / 1 Channel Output
- > User Friendly Graphical User Interface (GUI) Menu
- > Time Synchronization via the Internet or Network Time Servers
- > Up to 4 Simultaneous Connections through Web Browser or Client-Based Remote Software, with Live Viewing and Playback from a Remote Location
- > 4TB Maximum HDD Size = 1 HDD Bay (4 & 8 Ch) and 2 HDD Bays (16 Ch)



ADVANCED
TECHNOLOGY
VIDEO

960H, H.264 DVR

VLD904 / VLD908 / VLD916

VALUE LINE SERIES

SPECIFICATIONS

MODEL		VLD904-500GB, 1TB	VLD908-1TB, 2TB	VLD916-1TB, 2TB
V I D E O	Video Input	4 BNC Inputs	8 BNC Inputs	16 BNC Inputs
	Video Output	1 VGA, 1 BNC, 1 HDMI Outputs		
	Video Output Resolution	VGA: 800x600, 1024x768, 1280x1024, 1440x900, 1920x1080 HDMI: 1080p		
	Video Compression	H.264		
	Record / Playback Speed Frame Rate (DI) NTSC	120fps@CIF (360x240), 120fps@HD1 (720x240), 120fps@D1 (720x480)	240fps@CIF (360x240), 240fps@HD1 (720x240), 240fps@D1 (720x480)	480fps@CIF (360x240), 480fps@HD1 (720x240), 480fps@D1 (720x480)
	Record / Playback Speed Frame Rate (960H) NTSC	120fps@WCIF (480x240), 120fps@WHD1 (960x240), 120fps@WD1 (960x480)	240fps@WCIF (480x240), 88fps@WHD1 (960x240), 240fps@WD1 (960x480)	480fps@WCIF (480x240), 480ops@WHD1 (960x480), 480fps@WD1 (960x480)
	Recording Mode	Continuous / Manual / Event / Schedule / Sensor / Alarm		
	Playback Search	Date & Time / Event List / Time Bar		
	Playback Mode	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom		
G E N E R A L	Audio Input	4 RCA Inputs		
	Audio Output	1 RCA Output		
	HDD Interface	1 SATA		2 SATA
	HDD Support	Up to 4TB x 1	Up to 4TB x 1	Up to 4TB x 2
	Network Interface	RJ45, 10M/100M		
	Network Function	DHCP, PPPoE, Static IP, DDNS, P2P		
	PTZ Control	Terminal Block RS485 Built-In, supports PELCO-P & PELCO-D		
	# of Simultaneous Users:	4	4	3
	Alarm Inputs/Outputs	4 terminal block inputs / 1 terminal block output	8 terminal block inputs / 1 terminal block output	16 terminal block inputs 1 N.O. relay output; 3A@30VDC
	IR Port	1 Remote Control		
	USB	USB 2.0 x 2		
	Power Supply	12V / 2A	12V / 2A	12V / 5A
	Operating Temperature (without HDD)	14°F - 122°F (-10°C - 50°C)		
	Working Humidity	10% ~ 90%		
	Dimension (W x D x H)	13.4 x 9.1 x 2.7in (340 x 231.5 x 69mm)		
	Conformity Certifications	DVR: CE, FCC Power Adapter: UL, CE, FCC		

ACCESSORY

XDLBB2 Recorder Lockbox



DIMENSIONS

