

OLS180

Off-Line Switching Power Supply/Charger

Description

Altronix OLS180 power supply/charger converts a 115VAC, 60Hz input into a 12VDC or 24VDC output. This unit has a wide range of applications for access control and security system accessories that require additional power.



OLS180

Specifications

Input

Voltage 115VAC, 60Hz, 1.9A.

Outputs

Voltage 12VDC or 24VDC selectable.
 Current 6A continuous supply current.
 Other Short circuit and thermal overload protection.
 Filtered and regulated.

Back-up Battery *(not included)*

Type Sealed lead acid or gel type.
 Failover Upon AC loss, instantaneous.

Supervision

AC Failure Form "C" contacts.
 Battery Low/Fail Form "C" contacts.

Indicators (LED)

Input Input voltage is present.
 DC Output Powered.

Agency Listings

CE European Conformity

Physical and Environmental

Dimensions (L x W x H)
 7.25" x 4.5" x 1.75" (184.1mm x 114.3mm x 44.5mm).
 Product Weight 0.9 lbs. (0.4 kg).
 Shipping Weight 1.1 lbs. (0.5 kg).
 Temperature
 Operating 0°C to 49°C (32°F to 120°F).
 Storage -20°C to 70°C (-4°F to 158°F).
 Relative Humidity 85% +/-5%.
 BTU/Hr (approx.):
 12VDC: 37 BTU/Hr.
 24VDC: 74 BTU/Hr.

OLS180

Off-Line Switching Power Supply/Charger

Board Dimensions (L x W x H) and Drawing

7.25" x 4.5" x 1.75" (184.1mm x 114.3mm x 44.5mm)

