

Pace4PRM

IP and PoE+ over Extended Distance CAT5e Four (4) Port Receiver

Description

Altronix Pace4PRM is a long range Ethernet receiver that transmits data at 100Mbps full duplex and power via CAT5e or higher cable in a PoE(+) compliant format. Pace4PRM receiver is powered via a PoE midspan, such as the Altronix Netway series, or by an endspan. The receiver passes the PoE(+) compliant power over the cable to the Pace1PTM or Pace1ST transceiver which, in turn, passes this power to an enabled IP camera/device. These plug and play units facilitate cost-effective solutions for IP devices that need to be installed at the distances greater than 100m. They also provide a simple way to replace legacy analog products with new IP devices over structured cable.



Pace4PRM

Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W).
- Throughput is rated to pass 100Mbps.
- Eliminates the costs and labor associated with installing new network cabling.
- Retrofit digital IP cameras in an analog CCTV installation.
- Auto detection and protection of legacy non-PoE cameras/devices.
- Works with Megapixel, HD720, HD1080 & VGA (SD) cameras.
- Extends Network link distance in an industrial environment.
- Retrofit digital IP cameras in an analog CCTV CAT5e wired installations.
- UL Listed in the U.S. and Canada.
- CE Approved.
- C-Tick Compliant.
- Lifetime Warranty / Made in the U.S.A.

Compatible Transceivers:



Pace1ST

Pace1ST

IP and PoE+ over Extended Distance CAT5e Hardened Transceiver

Delivers IP video/data over CAT5e or higher up to 500m @ 100Mbps.

Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).

UL/cUL Listed (UL60950-1). CE Approved.



Pace1PTM

Pace1PTM

IP and PoE+ over Extended Distance CAT5e or UTP Transceiver

Delivers IP video/data over CAT5e or higher up to 500m @ 100Mbps.

Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).

UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



Pace4PRM

IP and PoE+ over Extended Distance CAT5e

Four (4) Port Receiver

Specifications

Input

Powered by midspan or endspan.

Ethernet

Connectivity: four (4) RJ45 ports, auto-crossover.

Wire type: 4-pair CAT5 or higher.

Distance: up to 500m.

Throughput is rated to pass 100Mbps of data.

With proper headend equipment multiple Megapixel cameras can be used.

Speed: 10/100BaseT, half/full duplex, auto negotiation.

Indicators (LED)

Yellow and Green LED (by RJ45 jack):
IP Link status, 10/100Base-T/active.

Agency Listings

UL/cUL

UL60950-1

(Information Technology Equipment).

CE

European Conformity.

C-Tick compliant.

Physical and Environmental

Dimensions (H x W x D)

1.7" x 5.25" x 8.42" (43.8mm x 133.35mm x 213.9mm).

Weight (approx.)

Product Weight: 1.35 lbs. (0.61 kg).

Shipping Weight: 1.7 lbs. (0.77 kg).

Temperature

Operating: -20°C to 49°C (-4°F to 120.2°F).

Storage: -30°C to 70°C (-22°F to 158°F).

Relative Humidity 85% +/-5%.

Operating Altitude: -304.8 to 2,000m.

Also Available:



Pace8PRM

Pace8PRM

Eight (8) Port Receiver

Transmits IP video/data over CAT5e or higher up to 500m @ 100Mbps.

Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).

UL/cUL Listed (UL60950-1). CE Approved.



Pace16PRM

Pace16PRM

Sixteen (16) Port Receiver

Transmits IP video/data over CAT5e or higher up to 500m @ 100Mbps.

Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).

UL/cUL Listed (UL60950-1). CE Approved.

Accessories:



NetWay8M

NetWay8M and NetWay16M

Provide input power for Pace receivers.

Eight (8) or sixteen (16) port managed midspans.

UL/cUL Listed (UL60950-1 and UL294). CE Approved.

