

#### Features:

In-wall microphone and line level pre-amplifier/mixer  
 Locking Stainless Steel cover plate  
 Fits most 2 gang electrical boxes  
 Provides volume control of input sources  
 Provides master volume control of-  
 Factor Electronics amplifiers  
 Two priority levels for momentary or continuous override  
 Switchable 100Hz HPF, 15dB pad and phantom power  
 Stereo RCA input automatically sums to mono  
 Stereo 3.5mm input automatically sums to mono  
 Locking balanced XLR/1/4" combo input jack  
 Connects to Factor amplifiers with Cat5/6 wire  
 Three VRVC-PRO units can be daisy chained-  
 on a single Cat5/6 run  
 All metal construction  
 Removable front panel knobs  
 Includes no-tamper security caps  
 Includes 2 x RJ45 crimp-on connectors  
 Includes 4 x white mounting screws  
 Can be used with any amplifier or pre-amplifier with  
 optional RVC-RJ45 Breakout adapter  
 Three year warranty!



#### Specifications:

Frequency Response – 20Hz – 20kHz  
 THD - <0.01%  
 S/N ratio Microphone – 70dB  
 S/N ratio Line – 80dB  
 Mic input sensitivity - -50dB to +10dBu  
 Line input sensitivity - -40dB to +14dBu  
 Power requirements – 24vdc - 300mA  
 (provided by Factor amps or V-RVC-RJ45 adapter)  
 Vox sens adjustment - Yes

#### MIC Input:

100 Hz high pass filter switchable  
 24vdc phantom power switchable  
 15dB microphone pad switchable

#### Global:

RVC remote master volume control switchable

#### Mute:

Latching mute switch provides silent source connections

#### Priority:

Latching shorting switch requires  
 2 additional wires connects to mute contacts on amplifier

#### Construction:

2 gang metal plate  
 Fits 2 gang mud ring or  
 2 gang metal or PVC back boxes

#### Front panel connections:

XLR/1/4" Combo balanced locking  
 RCA Stereo – sums to mono  
 3.5mm Stereo – sums to mono

#### Back panel connections:

RJ45 in  
 RJ45 out

#### Includes:

2 x RJ45 connectors  
 2 x Security keys  
 4 x white mntg screws

#### Dimensions:

Width – 4.50" / 114.5mm  
 Height – 4.54" / 115.5mm  
 Depth – 1.75" / 44.4mm  
 Weight – 2.2lb / 1.0kg

