



Features:

- 240 watt commercial mixer amplifier
- Four paging/music zones with zone volume control (global source)
- All-call paging to all zones simultaneously
- Seven inputs with individual volume control
- Onboard MP3 player plays music files from USB memory sticks or SD/MMC cards
- Four Mic/Line inputs on XLR/1/4" combo jacks
- Individually switchable phantom power on all mic inputs
- AUX input, Line Out + Pre-Out/Amp in
- Transformer isolated telephone input
- Dual MOH "Music on hold" outputs 600ohm balanced & 8ohm 1W
- 24V emergency operation
- Dual voltage switchable power supply 110V-60Hz/220V-50Hz
- Automatic reset protection circuitry
- Includes 2U rack mounting kit
- Three year conditional warranty
- CTUVus Listed



Optional Accessories:

V-RVC-PRO



In-wall mixer over Cat5/6

V-RVC-RJ45



Converts Cat5/6 to BAL line

X-Music



In-wall iPod dock over Cat5/6

Specifications:

AC Input Voltage 110-120V/220-240V Switchable

DC Input Voltage 24VDC

Amplifier Type Class A/B

RMS Power @ 4ohms - 240W

RMS Power @ 25V - 240W

RMS Power @ 70V - 240W

RMS Power @ 100 Volts 240W

RMS Power @ 24VDC 165W

S/N Ratio >80dB

Frequency Response (+/-3dB) 80Hz - 18kHz

T.H.D.@ Full Power 1.0%

Input Sensitivity Mic -52dBV balanced

Input Sensitivity Line -10dBV unbalanced

Input Sensitivity Aux -6dBV unbalanced

Input Sensitivity TEL -10dBV balanced

Thermal Protection 75 Degrees Celsius

Amplifier protection Overload, Thermal & Short Circuit

Output Connectors – Terminal Block screw type, RCA

Dimensions:

W -16.53" - 420mm

H - 3.5" - 89mm (2U)

D – 10.2" - 260mm

Shipping Weight:

24.2lb/11kg

Warranty Conditional:

3 years