



Overview

MCLASS™ Unified Power Systems combine FlexPower® power modules alongside Mercury Security™ access hardware in one compact and secure UL Listed solution.

The FPO Power Supply / Battery Charger provides two power outputs user selectable for 12 or 24 VDC. One output provides continuous output power for system use, the second is resettable output power, activated when the fire alarm disconnect is initiated.

For access or lock power, the D8P provides eight class 2 power limited outputs rated at 2.5A per output, each individually programmable for constant output or FAI disconnect.

MCLASS enclosures are painted steel with removable backplate and include lock, two (2) keys and tamper switch.



System Features

- ♦ **FPO offline power supply**
 - 120 or 230 VAC input
 - 12 or 24V DC outputs
 - On board Fire Alarm Interface
 - Continuous and resettable DC
- ♦ **Auxiliary outputs**
 - Eight, Class II power limited at 2.5A each
 - Each programmable to either continuous or resettable DC
- ♦ **Expansion options**
 - Increased power, multiple voltages
 - Additional distribution outputs
 - Network monitoring and reporting
- ♦ **Lifetime Warranty**

Enclosure Features

- ♦ **Labor saving design**
 - Pre-wired power section
 - Pre-punched knockouts
 - Removeable backplate simplifies installs
 - Pre-defined hole pattern for power section
 - Access panels mount on threaded standoffs - no drilling required
- ♦ **Additional benefits**
 - Wire management room
 - 4.5" enclosure depth fits battery set
 - Tamper switch, lock, dual key set standard
 - Mounting hardware for access boards included

Ordering

FP075-D8PE4M

Description

75W (12V or 24V) 8 auxiliary Class 2 outputs, MCLASS enclosure



Specifications

Input Power	Input 120/230 VAC 50/60 Hz 83 Watts (.70 Amps) Overload and short circuit protection Over temperature protection Polarized AC power supply disconnect
Output Power	FP075: 12V/6A or 24V/3A 75 Watts Outputs: Continuous (DC1) Resettable (DC2) 8 auxiliary outputs, class II power limited rated at 2.5 Amps per output 120 mV output voltage ripple System Efficiency: 83% System BTU Rating: 33 BTU/Hr
Battery Charging	Independent built-in 1A charger for sealed lead acid or gel type batteries Microprocessor dual rate charging of 12 or 24 V battery sets Charges up to 40Ah battery sets within UL limit Automatic switchover to standby battery when AC fails Zero voltage drop when switched over to battery backup
Supervision	AC Fail (form "C" contacts) System fail (form "C" contacts) may be triggered by low/no battery, short to earth ground, power supply failure or blown fuse
Visual Indicators	AC input, DC1 and DC2 output System fault AC fault Short to earth ground Reverse battery polarity Fire Alarm Input activated D8P: DC outputs
Regulatory Compliance	UL294, UL603, UL1076, ULC S318, ULC S319
Mercury/LSP	CSA C22.2 #107.1, CSA 22.2 #60950
Joint Listing	CSFM / FCC Part 15, Subpart B CE
Enclosure Dimensions	Size: 24.00H x 20.00W x 4.50D in. (61.00 x 50.00 x 11.50 cm) Weight: 25 lbs.
Access Panel Mounting	EP1501, EP1502, EP4502, EP2500, MR50, MR51e, MR52, MR16, LNL-500, 1100, 1200, 1300, 1320, 2000, 2210, 2220, 3300


Universal Mercury Mounting Pattern

E4M


Mercury	Slots w/Power	Slots all Mercury
MR52 / EPxx	4	6
MR16in / MR16out	4	6
EP2500 / MUX8	4	6
EP1501 / MR51e	8	12
MR50	8	12

E4M1 (adds six MR door panels)

Mercury	Slots w/Power	Slots all Mercury
MR52 / EPxx	10	12
MR16in / MR16out	10	12
EP2500 / MUX8	4	6
EP1501 / MR51e	8	12
MR50	8	12




UNIVERSAL MERCURY PATTERN all boards each slot




- (1) MR52 / EP1502
- (1) EP2500
- (2) EP1501 / Mr51E
- (2) MR50


E4M1 EXPANDS SIX MR52 TO D00R



E4M2 ON DOOR ONLY



E4M2 TWO VERTICAL



LifeSafetyPower.com

(888) 577-2898
info@lifesafetypower.com

Specifications subject to change without notice.

© 2017 LifeSafety Power Inc. All rights reserved. LifeSafety Power and FlexPower are registered trademarks of LifeSafety Power Inc. This literature is for guidance only. It does not constitute recommendations, representation, or advice, nor is it part of any contract. Our policy is one of continuous product improvement, and the right is reserved to modify the specifications contained herein without notice.

P01-661A 06/17

LifeSafety Power, Inc.
304 Terrace Drive
Mundelein, IL 60060 USA