



AC-G43



Outdoor Mullion Backlit PIN
Standalone Controller

AC-G44



Outdoor Mullion Backlit PIN & Proximity
Standalone Controller



Specifications		AC-F43	AC-F44	AC-G43	AC-G44
Input Voltage	VDC	12-24 V DC			
	VAC	16-24 V AC			
Max. Input Current (12VDC)		125mA	160mA	125mA	160mA
Standby Input Current (12VDC)		75mA	95mA	75mA	95mA
Max. read range*		N/A	75 mm (2.95")	N/A	80 mm (3.15")
Operating Temperatures		-32°C to 63°C (-25° F to 145°F)			
Operating humidity		0 to 95% (Non-Condensing)			
Outdoor usage		Weather-resistant, meets IP-65			
Size H x W x D		120.9 x 71.1 x 29.7 mm		135.4 x 74.2 x 28.5 mm	
		4.72 x 2.80 x 1.17 inch		5.33 x 1.74 x 1.12 inch	
Weight		244g (0.54 lbs)		178g (0.39 lbs)	

*Measured using Rosslare's AT-14 or equivalent. Range also depends on the electrical environment and proximity to metal.

ANTI-VANDAL PIN / PROXIMITY CONTROLLERS

These advanced 500-user standalone controllers feature a rugged metal casing ideal for installation in heavy traffic environments. With or without a built-in 125 KHz EM proximity card reader, these models are designed to withstand the rigors of the outdoor environment. They include a built-in keypad heater to prevent key freeze, and advanced programming options. Bell, chime, siren and strobe features are available with the BL-D40 accessory.

Major Features

- 500 dual-code users
- 2 x 2Amp Relays
- Three user levels and Three operation modes
- Selectable PIN code length: 4-8 digits
- Auxiliary input and auxiliary output
- Input for Request to Exit (REX) button
- Two tri-colored LED indicators
- Fully potted, meets IP65
- Optical case and back tamper protection
- Lockout feature on wrong entries (Keypad / Card Tamper)
- Bell, chime, siren and strobe features available with BL-D40
- Programmable keypad backlit options (some models)



MP-K01

Mount Spacer for K-Type Readers

- Compatible with AY-K12, AY-K14, AY-K20 and AY-K25 readers

MP-J01

Mount Spacer for J-Type Readers

- Compatible with AY-J12, AY-J14, AY-J20 and AY-J25 readers

MP-C02

Flush-Mount Housing for C-Type Keypads

- Compatible with AY-C09, AY-C19 readers, AC-C31 and AC-C32 controllers

MP-G02

Flush-Mount Housing for G-Type Readers and Keypads

- Compatible with AY-G54, AY-G64 readers and AYC-G54, AYC-G64 Convertible readers/controllers and AC-G43, AC-G44 standalone controllers
- Optional enclosure cover is available