

# Exit Switches



**410 & 420 SERIES**

The illuminated switch button is two inches square for easy activation and is visually conspicuous. The high impact resistant material stands up to abuse.

The "PUSH to EXIT" sign complies with NFPA requirements. The 422A is designed for access and egress applications for the disabled.



## MODELS

1 GANG	Narrow
<b>422</b>	<b>412N</b>
<b>423</b>	<b>413N</b>
<b>423P</b>	<b>413PN</b>
<b>424</b>	<b>414N</b>
<b>425</b>	<b>415N</b>
<b>422A</b>	
<b>423A</b>	



## SPECIFICATIONS

<b>Contact</b>	SPDT/DPDT, 5 Amp @ 30VDC Resistive
<b>Timer</b>	DPDT 2 Amp @ 12/24VDC
<b>Wire Leads</b>	6", 20 Gauge
<b>1 Gang</b>	2 7/8" x 4 1/2" x 20 Ga.
<b>Narrow</b>	1 3/4" x 4 1/2" x 20 Ga.



## HOW TO ORDER



**1 Gang:** 2" Button, Green Illuminated Button

**Narrow:** 1 3/4"x1" Button, Green Illuminated Button

### 1| SPECIFY MODEL

1 Gang	Narrow	Contact	Sign
<b>422</b>	<b>412N</b>	Momentary SPDT	PUSH TO EXIT
<b>423</b>	<b>413N</b>	Integrated electronic timer, adj. 1-60 sec, 12/24VDC, DPDT 2Amp contact	PUSH TO EXIT
<b>423PU</b>	<b>413PN</b>	Integrated pneumatic timer, adj. 1-180 sec. 12/24VDC, SPDT 3Amp contact	PUSH TO EXIT non-illuminated
<b>424</b>	<b>414N</b>	Momentary DPDT	PUSH TO EXIT
<b>425</b>	<b>415N</b>	AA (On/Off) DPDT	NONE

### 2" Button - Blue Illuminated button only

<b>422A</b>	Momentary SPDT	
<b>423A</b>	Integrated electronic timer, adj. 1-60 sec, 12/24VDC, DPDT 2Amp contact	

### 2| SPECIFY FINISHES

<b>U</b> Stainless Steel - Standard	<b>D</b> 606 Dull Brass
<b>C</b> 605 Bright Brass	<b>P</b> 625 Bright Chrome
<b>H</b> 613 Oil Rubbed Bronze	

### 3| SPECIFY OPTIONS

<b>L1G</b> 1 Green LED	<b>LT</b> Tri-color LED - Red, Green, Amber
<b>L1R</b> 1 Red LED	<b>R</b> Red Button in lieu of green
<b>L2</b> 1 Red, 1 Green LED	