Access

1,200-lb Electromagnetic Locks



E-941SA-1200 UL Listed

E-941SA-1K2PQ With bond sensor, status LED, UL listed

E-941SA-1K2PD With bond sensor, status LED, Timer

Features:

- 1,200-lb Holding force
- Anodized aluminum housing (US 28)
- Selectable 12/24 VDC operation
- No residual magnetism
- MOV surge protection
- Adjustable mounting bracket
- Complete mounting hardware for typical installations
- "L" and "Z" brackets available for easy mounting
- Detachable faceplate

E-941SA-1K2PQ Only:

- Built-in dual-colored status LED and bond sensor to indicate locking status
- Bond sensor relay rated 3A@12VDC

E-941SA-1K2PD Only:


- Built-in dual-colored status LED and bond sensor to indicate locking status
- Built-in timer: 1~78 seconds

Specifications:

Model		SA-1200	SA-1K2PQ	SA-1K2PD
Holding force		1,200-lb (545kg)		
Operating voltage		12/24 VDC±10%		
Current draw	12VDC	500mA@12VDC		
	24VDC	250mA@24VDC		
Bond sensor relay		3A@12VDC		
Operating temperature		14°~131° F (-10°~55° C)		
Weight		11-lb (5kg)		
Bond sensor relay			✓	✓
Status LEDs			✓	✓
Built-in timer				✓

E-941SA-1200 shown

Dimensions:



Additional brackets for easy mounting:

E-941S-1K2/ZQ	E-941S-1K2/LQ
"Z" Bracket	"L" Bracket
E-941S-1K2/HQ	E-941S-1K2/UQ
Armature Plate Holder	"U" Bracket



16842 Millikan Avenue, Irvine, CA, 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com

Copyright © 2016 SECO-LARM U.S.A, Inc. All rights reserved.

The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

(€®