

Indoor No-Touch Sensors



SD-927PKC-NEQ



SD-927PKC-NSQ



SD-927PKC-NFQ



SD-927PWCQ

Model Numbers

SD-927PKC-NEQ

Single-gang, stainless-steel faceplate, English message

SD-927PKC-NSQ

Single-gang, stainless-steel faceplate, Spanish message

SD-927PKC-NFQ

Single-gang, stainless-steel faceplate, French message

SD-927PWCQ

Single-gang, white plastic faceplate, English, French, and Spanish messages

Specifications

Model	SD-927PKC-NxQ		SD-927PWCQ
Operating voltage	12VDC		
Current draw	40mA@12VDC		
Relay type	Form C NO/NC/COM		
Switching capacity	3A@24VDC		
Response time	10mS		
LEDs	Standby	Green (selectable)	Red (selectable)
	Triggered	Red (selectable)	Green (selectable)
Output time	0.5sec or as long as sensor is triggered		
Range	4" (10cm)	2" (5cm)	
Operating temp.	-4°~131° F (-20°~55° C)		
Weight	3.0-oz. (85g)	2.5-oz. (70g)	

Features

- No-touch – just wave a hand in front of the sensor
- Sensing range up to 4" (10cm); sensing range up to 2" (5cm) for SD-927PWCQ
- Selectable LED color: Green to red or red to green
- SPDT relay output, 3A@24VDC
- Clean and simple no-touch operation reduces the risk of cross-contamination
- Reliable motion-sensing IR technology
- Durable, stainless steel, single-gang faceplate (except for SD-927PWCQ)
- Triggers a minimum of 0.5 sec, or as long as hand is near the sensor
- 12VDC Operation
- Current draw: 40mA@12VDC
- Dimensions: 2³/₄"x4¹/₂"x1⁵/₁₆" (70x115x33.5 mm)


Outdoor No-Touch Sensors



SD-9263-KSQ



SD-9163-KSQ



SD-9263-KSVQ



SD-9163-KSVQ

Model Numbers

SD-9263-KSQ

Single-gang, no-touch sensor

SD-9163-KSQ

Slimline, no-touch sensor

SD-9263-KSVQ

Single-gang, no-touch sensor with mechanical override

SD-9163-KSVQ

Slimline, no-touch sensor with mechanical override

SD-9263-KS1Q

Single-gang, no-touch sensor, Spanish message



SD-9163-KS1Q

Slimline, no-touch sensor, Spanish message



French versions also available
Contact SECO-LARM for Details

Features

- Weatherproof (IP65) construction for outdoor use
- Clean and simple no-touch operation reduces the risk of cross-contamination
- Adjustable sensor range up to 7" (18cm)
- SPDT Relay output, 1A@30VDC
- Adjustable trigger duration 0.5~20 seconds or toggle
- Selectable LED color: Green to red or red to green
- 12/24 VDC Operation
- Current draw: 25mA@12VDC, 32mA@24VDC
- SD-9263-KSVQ and SD-9163-KSVQ only:**
 - Manual override button function in case of power failure
- SD-9263-KS1Q and SD-9163-KS1Q only:**
 - Spanish versions