

Contractor Elite In-Ceiling Speaker Series



SPCE6T 6.5" 70V premium in-ceiling speaker, sold individually

Features

- Premium components and sound for commercial installations
- Magnetic baffle for easy installation and package includes both black and white colored grilles
- Built-in selectable 70V transformer with settings of 32W, 16W, 8W, 4W, 2W, 1W and 8 Ohms
- Dual positive and negative speaker terminals for easy chaining
- Safety loop built into back panel



11.26" (Dia.)



6.1" (D)

Specifications

RMS Power	60W
Max. Power.....	120W
Transformer Type	70V
Transformer Power Taps	32-16-8-4-2-1W and 8 ohms
Termination Type	Phoenix connector
Sensitivity (1W/1M).....	91dB
Maximum SPL	102dB
Driver Impedance	8 Ohms
Magnet Size and Material.....	14.4 oz. ferrite
Frequency Response Range..	50Hz-20kHz
Dispersion @ 1000Hz	130°
Driver.....	6.5" aluminum woofer, 1.2" PEI tweeter
Speaker Dimensions	11.26" (Dia.) x 6.1" (D)
Mounting Dimensions	10.44"
Minimum Mounting Depth.....	6.2"
Weight	11.46 lbs.
Material.....	ABS baffle, steel backcan
Color	Black baffle and includes white and black grilles