



# KRAMER

## Galil 6-AW

6.5-Inch, 2-Way On-Wall Outdoor Speakers

| Speakers



The Galil 6-AW on-wall outdoor speaker features a multi-tap power transformer for selecting  $8\Omega$  (bypassing the transformer) or 70V/100V power settings, which are suitable for an array installation. Suitable for outdoor installations and applications. Available in white or black

### FEATURES

IP 66 Certified - Withstands heavy showers and other outdoor conditions

Type - 2-way on-wall speaker

Woofer - 6.5" polypropylene cone

Tweeter - 1" silk dome

Impedance -  $8\Omega$

Power Handling - 40W RMS, 110W continuous program

Transformer Taps - 70V: 30W/15W/7.5W/3.7W/Off (Lo-Z); 100V: 30W/15W/7.5W/Off (Lo-Z)

Package Includes - 2 speakers (1 pair), u-mount brackets, grommets

Colors Available - Black and white



# KRAMER

## TECHNICAL SPECIFICATIONS

---

|                                    |  |
|------------------------------------|--|
| DESCRIPTION:                       | 2-way on-wall speakers   |
| FREQUENCY RESPONSE:                | 65Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB  |
| WOOFER:                            | 6.5" (165mm) polypropylene cone with rubber surround   |
| TWEETER:                           | 1" (25mm) silk dome  |
| IMPEDANCE:                         | 8Ω (transformer tap in off position)   |
| TRANSFORMER TAPS:                  | 70V – 30W/15W/7.5W/3.7W/Off (Lo-Z), 100V – 30W/15W/7.5W/Off (Lo-Z)   |
| SENSITIVITY:                       | 87dB SPL, 1W @1m   |
| MAX SPL:                           | Continuous: 102dB, peak: 105dB   |
| POWER HANDLING:                    | 40W RMS, 110W continuous program   |
| CROSSOVER FREQUENCY:               | 4.3kHz   |
| DIRECTIVITY FACTOR (Q):            | 3.9 averaged 1kHz to 10kHz   |
| DIRECTIVITY INDEX (DI):            | 5.9dB averaged 1kHz to 10kHz   |
| INPUT CONNECTORS:                  | Terminal blocks  |
| MATERIALS:                         | Frame, aluminum grill, steel brackets and ABS cabinet  |
| STANDARDS COMPLIANCE:              | IP66 compliant   |
| OPERATING TEMPERATURE:             | 0° to +40°C (32° to 104°F)   |
| STORAGE TEMPERATURE:               | -40° to +70°C (-40° to 158°F)  |
| HUMIDITY:                          | 10% to 90%, RHL non-condensing   |
| WEIGHT PER SINGLE SPEAKER:         | 2.8kg (6.2lbs) approx  |
| WEIGHT WITH MOUNTING KIT:          | 3kg (6.6lbs) approx  |
| SHIPPING WEIGHT (FOR PAIR):        | 6.6kg (14.6lbs) approx   |
| DIMENSIONS WITH MOUNTING BRACKETS: | 21.5cm x 22.5cm x 30.1cm (8.5" x 8.9" x 11.9"), W, D, H  |
| INSTALLATION CLEARANCE:            | Front panel to wall (with mounting bracket): 22.7cm (8.9"), back panel to wall (with mounting bracket): 3.8cm (1.5") |
| ACCESSORIES:                       | 2 mounting brackets (including 4 knobs and 4 mounting screws)  |
| OPTIONS:                           | BCP-2S speaker cable   |
| COLORS:                            | Available in white or black  |



# KRAMER

## CONFIGURATIONS

|            |  |
|------------|--|
| GALIL 6-AW | 6.5-Inch, 2-Way On-Wall Speakers - Black |
|------------|--|

|  |  |
|--|--|
|  | 6.5-Inch, 2-Way On-Wall Speakers - White |
|--|--|

